



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: C12Q 1/68	A2	(11) International Publication Number: WO 00/65088
		(43) International Publication Date: 02 November 2000 (02.11.2000)

(21) International Application Number: PCT/EP00/03636

(22) International Filing Date: 20 April 2000 (20.04.2000)

(30) Priority Data:
99303215.0 26 April 1999 (26.04.1999) EP(60) Parent Application or Grant
AMERSHAM PHARMACIA BIOTECH AB [/];
(.) ULFENDAHL, Per-Johan [/]; (.) WONG, Kin-Chun [/];
(.) ULFENDAHL, Per-Johan [/]; (.) WONG, Kin-Chun [/];
(.) ROLLINS, Anthony, John ; (.)

Published

(54) Title: PRIMERS FOR IDENTIFYING TYPING OR CLASSIFYING NUCLEIC ACIDS

(54) Titre: AMORCES SERVANT A L'IDENTIFICATION, LE TYPAGE OU LA CLASSIFICATION D'ACIDES NUCLEIQUES

(57) Abstract

A method is described for identifying a rather small set of extendible primers for use in the identification, typing or classification of a nucleic acid of known sequence having known polymorphisms. A matrix of primers and pairs of primer extensions is prepared and subjected to analysis by a set covering problem algorithm, e.g. a greedy algorithm or one which involves a Lagrangian relaxation heuristic. Sets of primers are described for use in the identification, classification or typing of an organism, allele or gene selected from class 1 HLA, class 2 HLA and 16S rRNA.

(57) Abrégé

L'invention concerne une méthode destinée à identifier un ensemble plutôt petit d'amorces extensibles utilisées dans l'identification, le typage ou la classification d'un acide nucléique d'une séquence connue possédant des polymorphismes connus. Une matrice d'amorces et de paires d'extensions d'amorces est préparée et soumise à une analyse à l'aide d'un algorithme de problème d'ensemble, par exemple un algorithme glouton ou un algorithme heuristique de relaxation lagrangienne. L'invention concerne également des ensembles d'amorces utilisés dans l'identification, la classification ou le typage d'un organisme, d'un allèle ou d'un gène sélectionné dans la classe 1 HLA, la classe 2 HLA et la classe 16S rRNA.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C12Q 1/68		A2	(11) International Publication Number: WO 00/65088 (43) International Publication Date: 2 November 2000 (02.11.00)
(21) International Application Number: PCT/EP00/03636 (22) International Filing Date: 20 April 2000 (20.04.00) (30) Priority Data: 99303215.0 26 April 1999 (26.04.99) EP (71) Applicant (for all designated States except US): AMERSHAM PHARMACIA BIOTECH AB [SE/SE]; Björkgatan 30, S-751 84 Uppsala (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): ULFENDAHL, Per-Johan [SE/SE]; Rapphonsvagen 10B, S-756 53 Uppsala (SE). WONG, Kin-Chun [SE/SE]; Ursviksvagen 2B, S-172 36 Sundbyberg (SE). (74) Agent: ROLLINS, Anthony, John; Nycomed Amersham plc, Amersham Laboratories, White Lion Road, Amersham, Bucks HP7 9LL (GB).			(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published Without international search report and to be republished upon receipt of that report.
(54) Title: PRIMERS FOR IDENTIFYING TYPING OR CLASSIFYING NUCLEIC ACIDS			
(57) Abstract A method is described for identifying a rather small set of extendible primers for use in the identification, typing or classification of a nucleic acid of known sequence having known polymorphisms. A matrix of primers and pairs of primer extensions is prepared and subjected to analysis by a set covering problem algorithm, e.g. a greedy algorithm or one which involves a Lagrangian relaxation heuristic. Sets of primers are described for use in the identification, classification or typing of an organism, allele or gene selected from class 1 HLA, class 2 HLA and 16S rRNA.			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	PS	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Description

5

10

15

20

25

30

35

40

45

50

55

5

10

PRIMERS FOR IDENTIFYING TYPING OR
CLASSIFYING NUCLEIC ACIDS

5

15

20

10

DNA-sequence analysis is rapidly becoming a standard tool in modern, molecular biology research. Examples of applications include: Sequencing of unknown DNA-sequences, Identifying novel genes in stretches of sequenced DNA, Predicting protein-sequence and -structure from DNA-sequence alone and Identification of known gene-variations (sometimes called "typing a gene").

25

15

30

20

35

Typing of a gene could be crucial in some applications. For instance, organ-donation requires that the "immunological signature" of the donor matches that of the receiver. This "signature" is mediated by the *Human Leucocyte Antigen (HLA)* complexes (also known as *Major Histocompatibility Complex, MHC*) on the cell surface, and the corresponding genes are among the most varied in the human genome. Considering the importance of organ donation, the shortage of organ-donors and the fact that an organ cannot be stored for any longer time-periods, a rapid and accurate typing of the HLA-genes is required in order to make most use of the organs available for transplantations.

40

25

45

30

Another application where a rapid and accurate identification of a gene is desired is when trying to identify unknown bacteria. A rapid identification of the bacteria causing the illness of a patient makes it possible to administer the correct medication early in the treatment of the disease, thus reducing the discomfort for the patient. Since every self-replicating organism so far studied use ribosomes when translating mRNA to proteins, analysis of one of the genes coding for the ribosome, for instance the 16S rRNA in the case of prokaryotes, could be used to identify the organism in question.

50

There are several ways in which a gene can be identified, with the conceptually easiest being to sequence the entire gene and then

55

CONFIRMATION COPY

5

10

15

20

25

30

35

40

45

50

55

looking at the result. The main drawback is that this approach is time-consuming, and not easily scaled up using conventional methodology. A new method, *Arrayed Primer EXTension (APEX)*, lacks this drawback. APEX works by immobilising a large number of primers to a solid surface, thus creating a DNA-chip. These primers are constructed to be consecutively overlapping over the entire gene of interest, so that every base in the gene will have a primer to its 5'-end. By adding fluorescently labelled dideoxynucleotides, the primers will then be extended by one nucleotide using the sample DNA as template. It will thus be easy to check which nucleotide was incorporated, which in turn tells you the entire sequence of the sample DNA.

Since some genes, like the HLA and 16S rRNA, have a large number of known variations, a prohibitively large number of primers have to be created in order to probe for all possible combinations of variant positions in the gene. Thus the array primer extension method APEX for resequencing would need more than 16,000 primers if all DQB alleles would be sequenced from a 500 bp long PCR fragment. If all DQB alleles in pairs should be combined the number of primers might be even higher which would be the situation for a heterozygote found in most individuals.

But this might not be necessary, if some variations always or never occur together. This needs to be studied though, and a way found to determine the least number of primers (and what their sequences are) required for unambiguously identifying those genes.

An object of this invention is to find and implement an efficient algorithm capable of doing just that. The algorithm should preferably also take into account the melting points of the primers, so that the extension reaction can take place under optimal conditions for all of the primers on the chip. It should also minimise the number of "self-extended" primers, i.e. primers that can extend themselves without any sample DNA. This algorithm is then to be tested and evaluated on the HLA and 16S rRNA-genes. HLA is chosen partly because of the importance of rapid typing of these genes, leading to the fact that there are many other methods to

5 which APEX can be compared. It is also because the HLA-genes are
"easy" to work with, since they rarely contain any insertions or deletions.
10 These kinds of variations in the gene could potentially create problems
when designing primers for APEX. The 16S rRNA, on the other hand,
5 contains insertions and deletions and can thus be used to see if the
algorithm can handle such variations.

15 The invention provides a method of identifying a set of
extendible primers for use in the identification, typing or classification of a
nucleic acid of known sequence having known polymorphisms wherein:

- 20 10 i) all possible nucleotide sequences of a chosen length of the
nucleic acid are identified and their corresponding extendible primers,
ii) at least one extendible primer is removed from the set
wherein the at least one primer removed identifies a segment of the nucleic
25 acid identified by at least one other primer.

15 Preferably the method includes between step i) and ii):

- 30 ia) potential extensions for each primer are identified with
respect to each nucleotide sequence,
ib) for each extendible primer the identified potential extensions
are compared to determine which pairs of sequences can be discriminated
20 by the primer.

35 Preferably a matrix of primers and pairs of primer extensions
is prepared in binary form and is subjected to analysis by a set covering
problem (SCP) algorithm as described in more detail below.

40 The invention also includes a set of extendible primers, for
25 use in the identification, typing or classification of a nucleic acid of known
sequence having known polymorphisms, identified by the method as
defined. Preferably the primers are attached by 5'-ends to a surface of a
45 support on which they are presented in the form of an array.

50 In another aspect, the invention provides a set of extendible
30 primers, for use in the identification, typing or classification of a human
leucocyte antigen (HLA) gene as indicated, the set comprising about the

number of primers indicated and being capable of distinguishing about the number of alleles indicated:

	HLA gene	Number of Alleles	Number of Primers
Class I	HLA-A	91	172
	HLA-B	200	<1000
	HLA-C	47	94
Class II	DPA-1	11	26
	DPB-1	74	130
	DQA-1	17	130
	DQB-1	34	84
	DRB-1	192	<1000
	DRB345	35	94

In another aspect, the invention provides a set of extendible primers, for use in the identification, typing or classification of 16S rRNA, wherein the set comprises about 210 primers and is capable of distinguishing at least about 1207 different sequences.

In these aspects of the invention, the approximate number of primers is indicated. As indicated below, it may be possible by the use of the algorithms exemplified or other algorithms to generate slightly smaller sets of primers capable of distinguishing the number of alleles or sequences indicated, and these sets are envisaged according to the invention. Of course, other primers may be present in addition to those indicated as essential, and may be useful for checking purposes. The number of alleles or sequences indicated represents the approximate known number of polymorphisms or different sequences, and these will surely increase with time.

In another aspect the invention provides a method of identification, typing or classification of a nucleic acid of known sequence having known polymorphisms, by the use of the set of extendible primers as defined, which method comprises applying the nucleic acid or fragments thereof to the set of extendible primers under hybridisation conditions and effecting template-directed chain extension of extendible primers that have

5
10
15
20
25
30
35
40
45
50
55

formed hybrids. Preferably template-directed chain extension is effected using four different fluorescently labelled chain-terminating nucleotide analogues, and results are analysed by an imaging system such as total internal reflection fluorescence (TIRF) or scanning confocal microscopy. The various steps of the method may be performed as described in the literature for the known APEX technique.

In another aspect the invention provides a kit for use in the identification, typing or characterisation of a nucleic acid of known sequence having known polymorphisms, comprising the set of extendible primers as defined.

In another aspect the invention provides an array of sets of extendible primers as defined, for the simultaneous identification, typing or classification of two or more different HLA genes.

With the present invention it has been realised that where a number of different alleles are to be identified, the total number of primers required to distinguish each of the alleles could be reduced as some primers would be common to all of the alleles, for example. Thus, with the present invention complete sets of primers for identification of each allele are identified and then the total number of primers in the combined sets is reduced using predetermined rules.

Furthermore the present invention is based on the premise that as the primers are used to identify the presence or absence of a particular nucleotide sequence in any allele, the specific nucleotide that extends any particular primer is of less relevance than simply whether the primer has been extended. Thus, the problem of reducing the overall number of primers is greatly simplified rendering the problem one suitable for treatment as a Set Covering Problem (SCP).

Embodiments of the present invention will now be described by way of example with reference to the accompanying drawings and examples, in which:

Figure 1 is a diagram of a signal matrix in accordance with the present invention;

5
10
15
20
25
30
35
40
45
50
55

Figure 2 is a diagram of the corresponding binary matrix for the signal matrix of Figure 1;

Figure 3 is a flow diagram of the steps for reducing the primer set in accordance with the present invention.

5
10
15
20
25
30
35
40
45
50
55

The following is an explanation to assist in an understanding of the principles underlying the manner in which the number of primers used in the identification of a plurality of sequences may be reduced.

Theoretically the number of primers required to identify k sequences grows as $O(k \cdot l)$, where l is the length of the sequences as each sequence requires l primers. However, the less the sequences differ from one another, the fewer primers are required as many of the primers required for identification of a first sequence may also be of use in identification of another sequence. This effect becomes more pronounced the greater the number of sequences to be identified and the greater the similarities.

Considering an initial set of n primers required in the identification of k sequences, a signal matrix of $k \times n$ can be constructed. Each element in the matrix represents the signal, if any, that is generated by a particular primer with respect to a particular sequence. The signal will either be one of the four nucleotides 'A', 'C', 'G', or 'T' or no signal '-'. Figure 1 is an example of such a signal matrix where, for example, the signal generated by primer 2 with respect to sequence 3 is 'T'.

The signal matrix is then converted into a binary matrix that represents whether the signals for any particular primer differ with respect to different sequences. Thus, again with respect to primer 2, the same signal 'G' is generated for both sequences 1 and 2 but a different signal 'T' is generated with respect to sequence 3. The binary matrix is constructed by considering each column (each primer) of the signal matrix and comparing each signal in that column in turn. Thus, as shown in Figure 2, the first row of the matrix represents a comparison of the signals for the first and second sequences, the second row represents a comparison of the signals for the first and third sequences and the third row represents a

5 comparison of the signals for the second and third sequences. Binary '0'
represents the comparison revealing the same signal and binary '1'
10 represents the comparison reveals different signals. In the case of primer
2, as mentioned earlier the signals for the first and second sequences are
5 the same ('0') whereas the signals for the first and third sequences are
different ('1'). This conversion produces a matrix $m \times n$ where $m = (k(k-1))/2$.
15 Hence, for large numbers of sequences, $2m$ grows approximately as the
square of the number of sequences. Figure 2 shows the binary matrix for
the signal matrix of Figure 1.

20 As the primers are required to enable the differentiation of
sequences from one another, the reduction of the signal matrix to a binary
matrix, representing differences in the signals obtained for different
sequences, distils that element of information necessary to enable a
25 selection of the minimum number of primers necessary to identify the
individual sequences. From the binary matrix the least number of columns
15 are selected such that each row contains at least one non-zero element.
Thus, if one of the columns contained all '1's only that one column would
be required. However, in the case of Figure 2, there is no single column
30 containing all '1's and so two columns must be selected, for example
primers 1 and 2. Primers 1 and 2 together enable each of sequences 1, 2
20 and 3 to be differentiated and so the remaining primers are redundant.

35 Where large numbers of sequences and primers are involved,
the binary matrix renders the data contained within that matrix suitable for
mathematical analysis. Once the selection of the reduced number of
40 primers has been made, though, it is the signal matrix that is required
25 during the use of the primers in the identification of the different sequences.
Thus, the signal matrix is used to 'decode' the results of any analysis using
the reduced number of primers.

45 In practice, large numbers of sequences and primers are
30 involved and the selection of a reduced set of primers cannot be performed
by simple inspection of the binary matrix. For large numbers of primers,
50 selection of a suitable reduced set of primers can be performed by treating

the selection as a Set Covering Problem (SCP). An SCP is an integer optimisation problem and is well known in fields such as airline crew scheduling, selecting manufacturing equipment and ingot mould selection in steel production. In such large scale problems that cannot be solved exactly (NP-hard), heuristics are used in order to generate a solution. As a SCP is NP-hard, global algorithms and algorithms that identify local optima are not very suitable on their own for a large scale SCP. They will simply require far too much computation, as they try to find a solution that can be proven to be at least locally optimal. For this reason heuristic methods are required instead. They do not claim to give even locally optimal solution, but are much faster.

Two known computational methods that have been found to be effective in identifying reduced sets of primers are the 'greedy' algorithm and Lagrangian relaxation algorithm.

Greedy Algorithm

The most simple heuristic is the *greedy* algorithm, where columns are added one at a time. The column to be added in each step is chosen so as to cover as many uncovered rows as possible (a row is covered if it has at least one non-zero element). In other words, if S_r is the set of columns already included in the solution at iteration r , and R_r is the set of rows with no non-zero elements at iteration r , column j_r^* is selected according to:

$$P_j = \sum_{i \in R_r} a_{ij}$$

$$j_r^* = \arg \min c_j / P_j \quad j \notin S_r$$

Equation 1

This continues until all rows are covered, or until no more columns exist which can cover any of the rows still uncovered. Instead of minimising the term c_j / P_j , other terms can be used. Example terms are c_j ,

$c_j / \log_2 P_j$ or $c_j / (P_j)^2$. Greedy algorithms of this type are described in "An Efficient Heuristic for Large Set Covering Problems", Vasko, Wilson, Naval Research Logistics Quarterly 1984, 31:163-171 the contents of which is incorporated herein by reference. The difference is in how much emphasis to place on the cost of the column versus how many rows the column covers. It is shown, however, that this entire class of heuristics share the same worst case behaviour. If we denote the set of columns in the solution as S and the solution value as Z , then the worst case behaviour can be described as:

$$\frac{Z_{heu}}{Z_{opt}} \leq H(d)$$

Equation 2

where

$$Z = \sum_{j \in S} c_j x_j$$

$$H(d) = \sum_{j=1}^d \frac{1}{j}, \quad d = \max_j \sum_{i=1}^m a_{ij}$$

Equation 3

In other words, how much worse the heuristic solution is compared to the optimal solution is dependent on the maximum number of non-zero elements in the columns. The advantage is that this algorithm is fast, even though its time complexity is $O(m^2n)$ (there can be a maximum of m columns in the solution, i.e. the maximum number of iterations is m . For each iteration the matrix is traversed once to find the next column to be added). Altogether, we have that the time required to solve the problem in the worst case scenario will grow as the number of sequences to the power of five (four due to the number of rows, and one due to the number of columns). In the case of 16S rRNA (see later), where we have ~1000 sequences, the matrix will have ~500,000 rows. The number of primers

(columns) is in this case ~250,000.

Lagrangian relaxation

More sophisticated methods exist, which use other kinds of heuristics. One heuristic capable of generating the most optimal solutions is believed to be some kind of *Lagrangian relaxation* heuristic, where in each iteration the Lagrange multipliers for each column are used to calculate the Lagrangian cost for the columns. Such a Lagrangian relaxation heuristic is described in "A Heuristic Method for the Set Covering Problem", Capara et al Technical Report OR-95-8, Operations Research Group, University of Bologna 1995 the content of which is incorporated herein by reference. A near optimal vector of these costs is then calculated by a *subgradient* algorithm, before being used as input to a greedy algorithm. This is repeated until no improvements in the solution can be made.

In Lagrangian subgradient methods the *Lagrangian* of the original problem is considered instead of the original problem. In this case, the Lagrangian will be

$$L(u) = \min \sum_{j=1}^n c_j(u) x_j + \sum_{i=1}^m u_i$$

$$x_j = \begin{cases} 0 \\ 1 \end{cases}$$

Equation 4

where u_i is the Lagrangian multiplier for row i . $c_j(u)$ is the Lagrangian cost associated with column j , and is defined by

$$c_j(u) = c_j - \sum_{i=1}^m a_{ij} u_i$$

Equation 5

An optimal solution to Equation 4 is given by

$$x_j(u) = \begin{cases} 0 & \text{if } c_j(u) > 0 \\ 1 & \text{if } c_j(u) < 0 \\ 0 \text{ or } 1 & \text{if } c_j(u) = 0 \end{cases}$$

Equation 6

$L(u)$ can also be seen as an estimate of the lower bound for the solution, i.e. the sum of the costs for the columns in the optimal solution to the SCP will be $\geq L(u)$. The solution to the SCP can be found by finding an optimal multiplier vector u^* instead, but this will require much computation especially for a large SCP. But near-optimal multiplier vectors can be found within short time by using the *subgradient* vector $s(u)$, defined by

$$s_i(u) = 1 - \sum_{j=1}^n x_j(u), \quad i = 1 \dots m$$

Equation 7

u can be refined iteratively by using for example

$$u_i^{k+1} = \max \left\{ u_i^k + \lambda \frac{UB - L(u^k)}{\|s(u^k)\|^2} s_i(u^k), 0 \right\}$$

Equation 8

where $\lambda > 0$ is a *step-size* parameter and UB is an upper bound on the value of the solution. The initial u^0 can be defined arbitrarily. To solve the SCP, first a near-optimal multiplier vector u is found. This and Equation 6 is then used as a basis to form a feasible solution. The upper bound UB can then be updated to the value of this feasible solution (if it is better than the previous best solution), and a new near-optimal multiplier vector found and so on until convergence is reached.

5

10

15

20

25

30

35

40

45

50

55

Another alternative computational method that may be employed to solve such a SCP is 'surrogate relaxation' in which in each iteration a corresponding continuous problem is solved and made feasible before a sub-gradient algorithm is applied. Alternatively, genetic algorithms may be employed in which the 'genome' consists of n bits, one bit for each of the columns.

It should also be borne in mind that as the SCP operates on the binary matrix which only represents differences in signals between sequences for the same primer, a primer in the selected reduced set may generate a negative, '-', signal rather than a positive signal, A, C, G, T. To be sure that the sample does in fact contain a particular sequence it is essential to ensure that for each sequence at least one primer generates a positive signal. Furthermore, in practice redundancy is desirable as all reactions may not occur as intended. Therefore, the least number of positive signals as well as the least number of differences in the signal pattern is preferably larger than one.

With reference to Figure 3, the following is a description of one method of selecting a reduced set of primers.

Firstly, all possible primers are selected (10) using the standard APEX procedure to produce a first set of primers. During this selection a substring of the sequence to be analysed is used to construct one primer, then the substring is displaced by one base and another primer is constructed. This process is carried out from the start of the sequence until the entire sequence has been covered. Both strands of DNA are used and this is repeated for all sequences. The primers should be long enough to be capable of discriminating between exact matches and mismatches involving one or two nucleotide pairs. Conveniently, the primers are 13bp long as this has been found to be sufficient to ensure the reaction, or longer to increase hybrid stability. However, to avoid steric hindrance on the chip each primer may be 5'-tailed. In this example, twelve 'T's are added to the 5'-end of the primer so that the final length of the primers is 25bp.

Next all primers that are not suitable as primers are rejected

5

10

(12) and the rest is included in a primary primer set. Unsuitable primers are those where the three bases at the 3'-end are complementary to any substring of the primer. In some instances this can result in the primer being extended by a neighbouring primer and not the sample DNA as a template and for that reason such primers are considered unsuitable.

15

Also, any primers that would produce ambiguous signals are identified and rejected (14). A primer produces an ambiguous signal where it is not known which of the four bases is in the relevant position.

20

Each of the remaining primers in the primary set primer is then compared to each sequence in turn to determine whether the primer is extendible by each sequence and if the primer is extendible the base with which it would be extended is determined. A signal matrix of the primers with respect to each of the sequences is thus generated (16).

25

30

In order for a primer to be extended using the sample DNA as template, the three bases in the 3'-end of the primer must hybridise to the DNA. Otherwise the enzyme responsible for the extension will not be able to add a nucleotide to the primer. Of the rest of the primer (the poly-T tail excluded), at most two mismatches are allowed, otherwise the primer-DNA duplex is considered to be too unstable to be extended.

35

40

In ordinary PCR, all the bases must match in order for the primer to be extended. But then the temperature is raised to the melting point, T_m , of the primer in the extension step. In APEX, this reaction is carried out at 45°C, which is around 10°-20° below T_m of most primers. This means that the primers will hybridise to the DNA despite a few mismatches, which is why two mismatches are allowed here.

45

50

In some cases a primer could hybridise to a sequence in more than one position, and sometimes a primer could hybridise to both strands of one allele and give different signals. In those cases all the different signals are combined to form one resulting signal (e.g. 'A' and 'C' together forms 'M', which is the NC-IUB (NC-IUB, 1985) code for this combination).

55

For each column of the signal matrix the entries for each row

5

10

15

20

25

30

35

40

45

50

55

are compared against one another, in other words for each primer the signals produced by the primer for each sequence are compared against each other. A binary matrix is thus generated (18) of the primers with respect to the identity or difference of signals for pairs of sequences. The binary matrix contains non-zero entries where the primer is able to distinguish between a pair of sequences.

The number of pairs of sequences that each primer can distinguish between are counted and a score is allocated to each primer (20) in dependence on the total number of pairs of sequences counted.

Thus, the number of non-zero elements for each primer are counted. Primers that are unable to distinguish between any pairs of sequences are rejected (22) and the remaining primers are sorted (24) in order of their score with the primers with the higher scores at the beginning.

A core of primers is created next (26). The primer with the highest score is selected. Where two primers with equal scores exist, the number of positive signals is determined for each and the primer with the greater number of positive signals is chosen. If both primers remain equal, one is then selected arbitrarily over the other. After the main primer has been selected, the first twenty (five times the desired redundancy which is four here) primers giving positive signals for each sequence in turn are selected for the core. All remaining primers are rejected.

A greedy algorithm is then run (28) using the core set of primers to identify the minimum number of primers necessary to distinguish each sequence. As the greedy algorithm is run, primers are added one at a time with each primer being selected in turn in relation to the number of uncovered rows it is capable of covering. When all rows are covered at least four times the reduced set of primers is checked for any sequences that has fewer than four positive signals and extra primers are added as necessary to meet this minimum requirement.

A redundancy check is then performed (30) to identify whether any more primers can be removed. During the redundancy check each primer is "tentatively" removed in turn to see whether the remaining

5

primers meet the minimum requirements.

10

If not, the next primer is tried. Otherwise the primer is temporarily removed from the set, and the process continues with the next primer in line. This process continues until no more primers can be

5

removed, in which case the last primer to be removed is added back to the set, and the next primer in line tentatively removed and so on. This can be viewed as a depth-first search of a tree where the nodes are combinations of primers, and the number of primers in each node is one less than in a node one level above. The root node thus contains all primers from the

15

20

10

greedy algorithm. It has p (the number of primers after the greedy algorithm) primers in it. It also has p child-nodes (because there are p ways in which you can remove one primer from a set of p primers), each with $p-1$ primers. Each of them has $p-1$ children with $p-2$ primers and so on. In this way, all possible combinations of primers in the set fulfilling the requirements are found, and those combinations with the same, least number of primers are saved as the final primer sets.

25

15

30

Instead of applying greedy algorithm to the core set a modified algorithm called CFT may be applied.

35

20

Lagrangian subgradient

40

This algorithm consists of three main phases: A subgradient phase where a near-optimal multiplier vector is found, a heuristic phase where a solution to the SCP is found and column-fixing, designed to improve the results of the heuristic phase.

25

In the subgradient phase, a near-optimal multiplier vector u is found using Equation 8. At the beginning, the starting vector u^0 used is defined as

45

$$u_i^0 = \min_j \frac{c_j}{\sum_{k=1}^n a_{kj}}$$

50

Equation 9

55

5

10

15

20

25

30

35

40

Later calls use the last vector u before column fixing, and apply a small perturbation before using it as the starting vector. The perturbation is randomly (and uniformly) distributed in the range $\pm 10\%$ for each element. The sequence of multiplier vectors is considered to have converged when the improvement in $L(u)$ in the last 50 iterations is smaller than 0.1%, or when the number of iterations reached $10 \times m$. The factor λ in Equation 8 was set to 0.1 at the beginning, and was updated as follows: Every 20 iterations, the best and worst lower bounds $L(u)$ during those 20 iterations are compared to each other. If the difference is larger than 1%, the value of λ is halved. If the difference is less than 0.1%, λ is multiplied with 1.5. In the first call, the upper bound, UB , used is the sum of the costs of the first primers that together cover all rows four times. Otherwise it is the value of the best solution found so far.

In the heuristic phase, the last vector from the subgradient phase is used to generate a sequence of multiplier vectors (again using Equation 8), and a feasible solution constructed for each of the multiplier vectors. The procedure used to generate a feasible solution is a variation of the greedy algorithm, where each column is scored according to

20

$$\begin{aligned}\mu_j &= \sum_{i \in R} a_{ij} \\ \gamma_j &= c_j - \sum_{i \in R} u_i^k \\ \sigma_j &= \begin{cases} \gamma_j / \mu_j & \text{if } \gamma_j > 0 \\ \gamma_j \times \mu_j & \text{if } \gamma_j \leq 0 \end{cases}\end{aligned}$$

Equation 10

45

50

55

where R is the set of uncovered rows in each step. The column with the lowest σ_j , i.e. the columns with the best "gain/cost"-ratio, is added in each step to the solution. This continues until no improvements to the best solution (i.e. minimum number of primers) have been made for 50 iterations.

After the heuristic phase column fixing is applied to the solution. Columns that are absolutely necessary in order for a row to be covered (i.e. if there are only e columns covering a row and each row is to be covered e times) are fixed. These fixed columns are then used as a starting point for the greedy algorithm, and the first $\max\{\lfloor 200/m \rfloor, 1\}$ columns chosen therein are fixed as well.

These three phases are then applied again to the problem, with the condition that the fixed columns must be included in the solution this time. Columns already fixed in a previous round can not be removed from the solution. This goes on until either all rows are covered by the fixed columns, or the cost of the fixed columns is larger than the estimated lower bound for the entire problem or if no new columns were fixed in the last iteration.

When the three phases are done, the problem is refined, in order to improve the solution. Here, each column in the best solution found so far is scored according to

$$\delta_j = \max\{c_j(u^*), 0\} + \sum_{i=1}^n a_{ij} u_i \cdot \frac{K_i - 1}{K_i}$$

Equation 11

where

$$K_i = |S| - \sum_{j=1}^n a_{ij}$$

Equation 12

and S is the set of columns in the solution. The term $u_i(K_i - 1)$ is the contribution of row i to the gap between the estimated lower and upper bound of the problem. This is then split uniformly between all columns in the solution covering that row. Columns with small δ_j (contributing the least to the gap) are then likely to be part of the optimal solution. The p columns with the smallest δ_j are then fixed before the entire

algorithm is applied again to the resulting sub-problem. (Column fixing here has nothing to do with column fixing after the heuristic phase, so columns fixed there need no longer be fixed here). p is the smallest value satisfying

$$\frac{|U_{j \in I_j}^{j_k}|}{e \times m} \geq \pi$$

Equation 13

where $\{j_k\}$ is the set of columns in the solution ordered with ascending δ_j , and I_j is the set of rows covered by column j . π is in the range 0...1 and controls the percentage number of rows removed after fixing. $\pi = 1$ means that no rows will be uncovered, while $\pi = 0$ means that no columns will be fixed before reapplying the algorithm. (Since each row has to be covered multiple times, in this case it is not actually the number of rows but the number of elements covering the rows that are regulated by π). In the beginning, π is set to 0.3 and is multiplied with $\alpha = 1.1$ if the best solution so far was not improved in the last application of the three main phases. If a better solution was found, π was reset to 0.3. Because of the density of the matrices, the number of columns fixed in this step was also set to be at least one more than in the previous iteration (if no improvements were made). Otherwise the same number of columns would be fixed in a number of iterations before the value of π is large enough to allow more columns to be fixed.

The algorithm is iterated until either the value of the best solution is less than the estimated lower bound, all columns in the best solution found so far are already fixed in the refining step or a time limit is exceeded. The time limit in this case was arbitrarily set to as many seconds as there were rows in the problem. However, the time limit is only checked before the refining step. If it is not exceeded, a whole iteration of the algorithm will be executed before another check is done. Here too a

5

check was done afterwards to see if primers could be removed without breaking any constraints.

10

With this algorithm no pricing is performed. Pricing is used to update the core problem, exchanging columns between the core problem and columns outside the core. It was not included here since it was argued that since the costs of the columns are all the same, the best columns would be those with the largest number of non-zero elements. These would be the first columns to be added to the core, and the columns not included in the core would most probably not be better than those included. Also, the pricing step will require some computation which will extend the time required by this algorithm. As is, the computational requirement of this algorithm is several orders of magnitudes higher than for the greedy algorithm. Finally, the main memory available in the computer puts a limit on the how large the problems can be. If pricing was included all data will not fit into the physical memory, forcing the computer to use a swap-file which would increase the computation times considerably.

20

25

30

Using both alternative algorithms described above a minimum number of primers were identified for various sequences. The results are set out below.

35

40

It will be apparent that the initial manual rejection of primers, steps (12, 14 and 22) need not be performed and instead the algorithms can be applied to the original complete set of primers. However, the initial rejection of obvious failed primer candidates can significantly reduce the computational time required in the later stages. Similarly, in many cases the final redundancy check (30) need not be performed as in many cases little or no reduction in the number of primers was achieved by this final check.

45

50

Furthermore, although in the method described above the primers were initially sorted in order of score, this need not be performed. The algorithms for stripping out redundant primers are capable of operating with any order of primers including a wholly random order. However, slightly better results were obtained when ordering by score was

55

performed.

Collecting sequences

The HLA-sequences were available internally from Amersham Pharmacia Biotech (release December 1997), and included 91 alleles from HLA-A, 202 HLA-B, 47 HLA-C, 11 HLA-DPA1 (coding for the α -chain), 74 HLA-DPB1 (β -chain), 18 HLA-DQA1, 34 HLA-DQB1, 192 HLA-DR1 and 35 sequences in all of HLA-DR3, -DR4 and -DR5. The length of these sequences range from ~250bp to ~1100bp.

The 16S rRNA-sequences were collected from GenBank (Benson *et al.*, 1998), an annotated database of all publicly available DNA sequences. Only a subset of all the available 16S rRNA-sequences were used. The sequences used were all from organisms that could be identified using either the *MicroLog* or the *MicroStation* system from Biolog Inc., or the *API* systems from CounterPart Diagnostics. These systems utilise differences in metabolism in order to identify the organisms, which is the most common way of identifying micro-organisms today. Altogether, 1207 sequences from 523 different organisms were collected from GenBank. 269 of those 523 organisms had only one 16S rRNA sequence among those 1207 sequences. The length of these sequences is between ~1000bp and ~1500bp.

Data set	No. sequences	Mean length of sequences
DPA1	11	517
DPB1	74	288
DQA1	17	616
DQB1	34	490
DRB1	192	324
DRB345	35	400
HLA-A	91	944
HLA-B	200	900
HLA-C	47	1003
16S rRNA	1207	1452

Table 1: Details about data sets.

The program was written using the Microsoft® Visual C++®, version 5.0 compiler. It was executed on a PC with a Pentium® MMX 233 MHz processor, 64 MB RAM and Windows® 95, unless otherwise indicated. All execution times are for the entire program, including I/O.

As can be seen in Table 2, the binary SCP matrices were quite dense. The density (i.e. the number of non-zero elements in the matrix) usually lies around a few percent, of course depending on the application. A higher density means that fewer columns are needed in order to cover all rows. This is offset in this case by the fact that all rows were required to be covered multiple times. Another consequence of this high density is that the number of primers needed according to the greedy algorithm could be much higher than in the optimal solution. (Recall that the worst case behaviour of the greedy algorithm is a function of the largest column-sum of elements.)

Dataset	DPA1	DPB1	DQA1	DQB1	DRB1	DRB345	HLA-A	HLA-B	HLA-C	16S rRNA
No. rows	55	2701	136	561	18336	595	4095	19900	1081	727821
Density (%)	47.89	20.73	36.31	42.18	24.98	37.70	36.31	32.33	30.41	2.04

Table 2: Some details about the binary SCP matrix. Data are calculated for all primers in the primary set.

The program could be considered as consisting of two phases. The first phase involves constructing all primers and finding out what kind of signal they will get for each sequence. The second phase is the optimisation phase, where the SCP is solved. Some details about the first phase can be found in Table 3.

Dataset	DPA1	DPB1	DQA1	DQB1	DRB1	DRB345	HLA-A	HLA-B	HLA-C	16S rRNA
First set	1747	1885	2487	2891	3891	3031	4756	4994	4293	247877
Primary set	1333	1475	2166	2730	3651	3016	3886	4585	3354	247877
Core set	106	321	213	244	385	203	595	750	338	2377
Time (s)	4.67	6.81	11.26	18.51	42.29	14.56	124.74	286.82	61.29	150632

Table 3: Number of primers in different stages of the algorithm and time to get signals for all primers. The number of primers in the core are for homozygotes.

5

10

15

20

25

30

35

40

45

50

55

One explanation to this high density is that the sequences in the data sets are quite similar to each other, so that most primers will hybridise to and give signal for more than one sequence (either the same or different signals). This is also indicated in Table 3, where for some data sets there is a noticeable drop from the number of primers in the first set to the number of primers in the primary set. Most of this reduction is due to a primer having the same signal for all sequences, which in turn means that all sequences have a substring that is similar enough for the primer to hybridise to and that the nucleotide after the primer is the same for all sequences. In contrast, the 16S rRNA data set has a much lower density, and no reduction in the primers going from the first set of primers to the primary set. As the sequences in this data set come from organisms which might be only distantly related to each other, there need not be as much similarity between the sequences as there is in the HLA data sets. Another explanation is this: If all k sequences except one give the same signal for a primer, that column in the binary SCP-matrix will have $k-1$ non-zero elements. The density (for that column) will then be $(k-1) / (k(k-1)/2) = 2/k$. In other words, the density will be higher for smaller values of k , and smaller for larger values. This means that it would be "natural" for smaller matrices to have higher densities, and larger matrices to have lower densities.

In the second phase, solving the SCP, a few different approaches were tried. The results, the minimum number of primers needed and the time required to find this number, can be found in Table 4 and Table 5. Even though the worst case behaviour of the greedy algorithm is not so good in this application, the results are not much worse than when using a Lagrangian subgradient (CFT) method. The greedy algorithm typically needs two or three more primers, while the computation times are much lower for the greedy algorithm.

The results show that it is worthwhile to check the results from the greedy algorithm for redundancy. In all cases except one primers could be removed and the resulting primer sets still fulfil all requirements.

This is not true for the CFT algorithm, however, as there is only one instance in which the result could be improved. On the other hand, since there is some randomness in the CFT algorithm (an old multiplier vector is disturbed randomly before being used as a starting vector in the next iteration), the results can differ from one execution of the algorithm to another. Sometimes the results can be improved, and sometimes not (results not shown).

Dataset	DPA1	DPB1	DQA1	DQB1	DRB1	DRB345	HLA-A	HLA-B	HLA-C	16S rRNA
Greedy	11	42	32	31	48	24	73	103	51	210
Time (s)	0.27	1.37	0.61	0.71	11.5	0.66	4.61	31.36	1.15	9921.48*
Final	11	41	30	29	44	21	72	99	47	197^
Total (s)	0.27	1.81	0.72	0.88	30.3	0.71	6.48	85.14	1.76	>300000^

Table 4: No. of primers after the greedy algorithm and time spent by it. Also final nr. of primers after check for redundancy and the total time spent solving the SCP. *Value from a 300MHz Pentium II with 512MB RAM running Windows NT 4.0. ^The computation was halted before completion due to time constraints.

Dataset	DPA1	DPB1	DQA1	DQB1	DRB345	HLA-A	HLA-C
CFT	10	38	26	27	20	69	47
Time (s)	10.22	2748.92	60.80	372.56	427.32	4547.33	1091.37
Final	10	38	26	27	20	69	45
Total (s)	10.22	2749.14	60.86	372.61	427.38	4548.49	1111.70

Table 5: Results using modified algorithm CFT.

One reason CFT is not much better than the greedy algorithm could be that it was designed for other instances of SCP. The SCP arising in this application differ in three aspects from those: A) The density is much higher, B) All rows are to be covered multiple times and C) The costs of all columns are all the same.

A comparison was made between the results from the greedy algorithm and from CFT in Table 6. Most of the primers (70% or more) were chosen by both algorithms, indicating that these primers are likely to

be part of an optimal solution. However, this is only an indication as the only way to prove this is to find an optimal solution. This will require far too much time even for the smallest data set as the problem is NP-hard.

Dataset	DPA1	DPB1	DQA1	DQB1	DRB345	HLA-A	HLA-C
Greedy	11	41	30	29	21	72	47
CFT	10	38	26	27	20	69	48
Same	7	33	22	22	14	62	38
Percent (%)	70.00	86.84	84.62	81.48	70.00	89.86	80.85

Table 6: Comparison of primers from the two different algorithms.

Results from combining HLA sequences in order to differentiate between heterozygous individuals can be found in Table 7.

CFT was only used for the two smallest data sets due to the time requirements. It performed slightly better than the greedy algorithm on those, but only by one primer on each data set. There are heterozygotes that can not be distinguished from another heterozygote, which can be seen in Table 7. This happens because the combination of two sequences to form one heterozygote could result in exactly the same signal pattern as another combination of homozygotes. In other words, some rows in the signal-matrix will be the same leading to some rows in the binary SCP-matrix not containing any non-zero elements at all. For some of those pairs listed, this is not true, however. They are listed because there were not enough primers that have different signals for these pairs, and so could not meet the requirement of at least four different signals in the signal patterns (Table 8). For the rest, it is simply a limitation of this technique to type HLA-genes. To be able to identify the alleles forming each heterozygote, primers that amplify alleles selectively should be used in the PCR step. This will remove the ambiguities as some heterozygotes simply will be transformed to homozygotes since only one of the alleles in the heterozygote will be amplified and not the other.

Dataset	DPA1	DPB1	DOA1	DOB1	DRB345	HLA-A	HLA-C
Greedy	26	130	51	81	94	172	94
Time (s)	0.99	9229.57	7.41	294.51	453.19	20826.20*	1212.59
CFT	25	-	50	-	-	-	-
Time (s)	1943.82	-	8427.82	-	-	-	-
Amb. het.	0	16	2	2	6	19	4
Percent (%)	0.00	0.58	1.31	0.34	0.95	0.45	0.35

Table 7: Results from heterozygous pairs. Number of primers needed, the time spent, how many heterozygotes that did not differ by at least four signals from any other heterozygote and the percentage of total number of heterozygotes. *Value from a 300MHz Pentium II with 512MB RAM running Windows NT 4.0.

Unfortunately, it was not possible to obtain any results for heterozygotes for the data sets DRB1 and HLA-B, as these were too large to run on existing machines. A very approximate extrapolation of the primers needed for these data sets suggests that the total number of primers for all HLA sets together would be <1000, which can be placed on one chip without problem (one chip can contain up to ~5000 primers). Without the reduction obtained above, at most two genes could be tested on each chip. With the reduction, all nine HLA genes and the 16S rRNA gene can be tested on one chip, and with plenty of room to spare for other genes as well. This makes APEX more versatile, as it allows a family of related genes to be tested using only one chip instead of several.

DPB1			SGA1			HLA-A		
Pair 1	DPB1*0501	DPB1*2101	Pair 1	DQA1*0101	DQA1*0104	Pair 1	A*0101	A*2411N
Pair 2	DPB1*2201	DPB1*3801	Pair 2	DQA1*0101	DQA1*0105	Pair 2	A*0104N	A*2402
No. diff.	2		No. diff.	3		No. diff.	0	
Pair 1	DPB1*0501	DPB1*5501	Pair 1	DQB1*0504	DQB1*0512	Pair 1	A*0201	A*0203
Pair 2	DPB1*3001	DPB1*0301	Pair 2	DQB1*0503	DQB1*0508	Pair 2	A*0202	A*0208
No. diff.	2		No. diff.	2		No. diff.	1	
Pair 1	DPB1*0601	DPB1*3501	Pair 1	DRB4*0101	DRB4*0101N	Pair 1	A*0201	A*0203
Pair 2	DPB1*2001	DPB1*2101	Pair 2	DRB4*0101	DRB4*0301N	Pair 2	A*0214	A*0222
No. diff.	1		No. diff.	0		No. diff.	1	
Pair 1	DPB1*0801	DPB1*1401	Pair 1	DRB4*0101	DRB4*0103	Pair 1	A*0201	A*0208
Pair 2	DPB1*1001	DPB1*5701	Pair 2	DRB4*0103	DRB4*0301N	Pair 2	A*0203	A*0220
No. diff.	0		No. diff.	C		No. diff.	0	
Pair 1	DPB1*0801	DPB1*3001	Pair 1	DRB4*0201	DRB4*0201N	Pair 1	A*0201	A*0213
Pair 2	DPB1*1701	DPB1*5401	Pair 2	DRB4*0201	DRB4*0301N	Pair 2	A*0213	A*0228
No. diff.	0		No. diff.	0		No. diff.	2	
Pair 1	DPB1*0901	DPB1*3501	Pair 1	Cw*1203	Cw*1602	Pair 1	A*0201	A*2408
Pair 2	DPB1*2101	DPB1*3501	Pair 2	Cw*12042	Cw*1601	Pair 2	A*0222	A*2413
No. diff.	0		No. diff.	0		No. diff.	0	
Pair 1	DPB1*0801	DPB1*4501	Pair 1	Cw*12042	Cw*1502	Pair 1	A*0202	A*0208
Pair 2	DPB1*1001	DPB1*1401	Pair 2	Cw*1205	Cw*1503	Pair 2	A*0214	A*0222
No. diff.	0		No. diff.	0		No. diff.	0	
Pair 1	DPB1*3001	DPB1*5301				Pair 1	A*0212	A*2801
Pair 2	DPB1*4001	DPB1*4901				Pair 2	A*0222	A*2808
No. diff.	0					No. diff.	2	
						Pair 1	A*2402	A*2502
						Pair 2	A*2407	A*2501
						No. diff.	0	
						Pair 1	A*2402	A*68012
						Pair 2	A*2407	A*68031
						No. diff.	0	
						Pair 1	A*2501	A*68012
						Pair 2	A*2502	A*68031
						No. diff.	0	

Table 8: Heterozygous pairs that do not differ enough in their signal patterns, and how many signals they differ with.

The results of this work are summarised in the following

Table 9

5

10

15

20

Class 1	Number of alleles	Primers needed	Class II	Number of alleles	Primers needed
HLA-A	91	172	DPA1	11	26
HLA-B	200	<1000	DPB1	74	130
HLA-C	47	94	DQA1	17	51
			DQB1	34	84
			DRB1	192	<1000
			DRB345	35	94

Table 9. Number of primers needed to discriminate between heterozygote HLA samples.

25

5

Some sets of primers indicated in Table 9, and also the set indicated for 16S rRNA, are set out in appendix 2.

30

10

Primers can be arranged on the surface of a support in such a way that different studied types, genes, alleles, species etc. form easily recognised characters such as figures or letters. These character forming primers can be additional primers of common origin from the gene of interest and be used for validation of the process.

35

The following demonstration is based on the HLA Class II DQB gene.

40

15

Experimental

Materials

45

Amplification:

20

DNA: Four homozygote for DQB cell lines, with alleles 0402, 0301, 06011 and 0201.

50

Primers: Primer DQB 9246 from Williams *et al.* -96 and DQB 96012 from Amersham Pharmacia Biotech HLA DQB typing kit, covering exon 2,

55

5

generating a fragment of 300 base pairs.

10

Amplification reagents: PCR mix from the Amersham Pharmacia Biotech
HLA DQB typing kit, a prototype kit.

All amplifications were spiked with dUTP, to get a final concentration of 100
5 or 200 mM dUTP.

15

Enzymes for fragmentation of PCR products:

Shrimp alkaline phosphatase (SAP) 1 U/ μ l APB.

Uracil-DNA-glycosylase, (if from PE UDG = UNG) 1 U/ μ l NE Biolabs.

20

10

SAP will degrade (dephosphorylate) all free dNTPs and UDG
will remove all dU from the DNA and after heating the strands will be
broken at these points. This step is applicable to any DNA fragment.

25

15 Primers for spotting:

30

All 84 primers for the 500 bp fragment were ordered from
LTI/GIBCO BRL Custom primers service. All were 25-mers with an amino-
activated 5' -end. For primer sequences see appendix 1. Self extended
primers were N, A, C, G and T as controls with the following sequences:

35

20 N: amino TTT AGC CTT AAC GCC T N TGAC GTCA

A, C, G, T: amino TTT AGC CTT AAC GCC T X TGAC GTCA, where X is
A, C, G or T.

40

Extension reagents for the APEX reaction

25 Dyes: Specially synthesised for Baylor by Du Pont and /or APB

Cy2 - ddCTP (equal to fluorescein) 50 μ M

45

Cy3 - ddATP 50 μ M

Texas Red - ddGTP 50 μ M

Cy5 - ddUTP (often written as T in many of the reactions and
results) 50 μ M

30

10x ThermoSequenase™ DNA polymerase buffer (TS):

50

55

5

10

260 mM Tris-HCl pH 9.5; 65 mM MgCl₂, ThermoSequenase DNA
polymerase (Amersham Pharmacia Biotech) 4 U/μl, if needed dilute with
T.S. dilution buffer (=10 mM Tris-HCl pH 8.0; 1 mM β-mercaptoethanol,
0.5% Tween – 20(v/v), 0.5% Nonidet P-40 (v/v). TS was used from a 150
unit stock and diluted 1 μl + 37 μl dilution buffer.

15

Methods

Preparation of glass slides before spotting of primer:

20

10 Arrange 25-30 cover slips (24 x 60 mm) in a stainless staining
tray.

Immerse the tray in glass staining dish with acetone to fully
immerse slides.

25

Place the glass staining dish in sonicator for 10 minutes.

15 Remove the tray from acetone bath, shake of excess of
acetone and rinse several times (at least twice) in MilliQ water.

30

Immerse tray in 100 mM NaOH and sonicate for 10 minutes
(a few more minutes, no problem).

Remove the tray and shake of excess of NaOH and rinse
several times (at least twice) in MilliQ water.

35

20 Immerse tray in silane solution and sonicate for 2 minutes.

Wash slides by immersion in 100% EtOH once.

Dry the tray with the slides using nitrogen with a high velocity
(without breaking the slides).

40

25 Cure the slides in a vacuum oven at 100°C over night or until
they are used for spotting (at least 20 minutes vacuum is needed).

45

Spotting of oligos:

All spotting was done with a spotter with 96 parallel capacity.

Each slide was spotted with three replicas of the primers.

50

30 After spotting the slides were allowed to air dry for 5 to 15
minutes, when dried they were marked. They were stored at room
temperature, in a dry place, in the trays until used.

55

5

DQB amplification

10

The DQB amplification was done according to the method described by Williams et al. -96 using a 33% dUTP mix. After 40 cycles (95°C, 30 sec.; 55°C, 30 sec.; 72°C, 30 sec.), one microliter of the PCR products was tested on a 1.5% agarose gel, before the fragmentation step.

15

Williams, Bassinger, Moehlenkamp, Wu, Montoya, Griffith, McAuley, Goldman, Maurer: Strategy for distinguishing a new DQB1 allele (DQB1*0611) from the closely related DQB1*0602 allele Tissue Antigens, 1996, 48:143-147.

20

10

Fragmentation of PCR products:

25

Before APEX can be done all DNA fragments must be fragmented so all new fragments can get access to the primer on the chip.

30

15 Set up:

35

5 µl DNA from a PCR reaction (1/10 of the PCR reaction)

2 µl SAP (Shrimp alkaline phosphatase) 1U/µl APB

1 µl UDG (Uracil-DNA-glycosylase) 1U/µl NE Biolabs

15 µl water

40

20 Total: 23 µl

Incubate 37°C for 2 hour.

The samples were frozen and stored until they were used.

45

Inactivation of enzymes at 100°C for 10 minutes can be done, but not needed since this is the first step in the APEX reaction.

25

Extension method for the APEX reaction

50

Slide treatment:

55

Start with washing the slides in hot water (90 - 98°C, not boiling) for 2 x 5 minutes in a 50 ml Flacon tube. When the slides are ready, remove them from the tube with a forceps and place them on a dry

5

heater block at 48°C. The slide(=DNA chip) is now ready for adding the reactions.

10

APEX reactions set up:

5

15

23 µl DNA from the fragmentation step.

3 µl 10x TS reaction buffer (the rest of the buffer comes from PCR and UDG cleavage)

17 µl for cover slip method.

20

10 Heat denature at 100°C for 7 – 10 minutes, target 8 minutes, not longer.

Spin the tube quickly and add quickly

1 µl ThermoSequenase DNA polymerase (4U)

25

1 µl Dye-mix (50 µM of the four dideoxynucleotides A, C, G, and T, separately dye labelled).

15

Then the reaction mix was physically spread out over the primer array with the tip of a pipette tip. Incubate at 48°C until no trace of solution is seen. This takes about 8 minutes.

30

Wash with hot water for 2 – 5 minutes, 2 times. Ready to read on detection instrument.

35

20

Detection

40

The detection system is a total internal reflection fluorescence (TIRF) system, where microscopic slides are placed on top of a prism with oil on to link a laser beam in to the glass slide. The system has light of five different wave lengths from five different lasers to vary between. In this experiment only four were used. To detect Cy2 a laser with 488 nm was used, for Cy3 a 532 nm, for Cy5 a 635 nm and for Texas Red a 670 nm laser were used. Image related software were based on Image Pro Plus 3.0.

45

30

50

55

5

Results

10

Amplification of HLA DQB alleles

15

The DNA from the four DQB homozygote cell lines were amplified according to the protocol in Williams *et al.* -96 with two different concentrations of dUTP. In addition to this, DNA from six different heterozygotes were amplified. All amplifications worked well and the expected 300 bp fragment were seen from all samples.

20

10 APEX reaction with DQB chip

25

Primer chips were washed and fragmented PCR products were incubated on the chip according to the protocol. The image was compared to the expected pattern. The expected pattern was similar to but somewhat different from the recorded pattern, the reason for this is that the set up was planned for a 500 bp fragment, but the actual fragment used was a 300 bp PCR fragment.

30

Homozygous cell lines results

35

Figure 4 shows the results from a cell line homozygous for the DQB 0204 allele. The pattern shown in the image is very close or similar to the expected results from exon 2.

40

In all reaction the control primers worked well and the four dyes were used in the same frequencies. In the case with a 500 bp fragment for DQB typing the primers for allele 0402 were placed in such a way that they formed figures. In Figure 4, panel D, most signals are seen forming a "2" from the 300 bp fragment, and the missing signal will be seen when the large PCR fragment is used. This clearly shows that primers can be placed in a clever way to form figures.

45

30 Heterozygous results

50

For the heterozygous test only one of the four dye reactions worked. Some of the expected spots from the heterozygous sample were

55

5

not seen, but this is probably due to the fact that no control signals were seen in the lower right hand corner, where the signals were weaker than in other part of the slide.

10

As this experiment shows, a limited number of primers can be used for HLA typing and if they are placed in a clever way the interpretation of the results is very simple. Both homozygous and heterozygous samples can be correctly analysed with this method.

15

Continuation

20

An algorithm was developed in order to select the minimum number of primers needed to identify different genes using APEX. It was applied to the following HLA genes: HLA-A, HLA-B, HLA-C, HLA-DPA1, HLA-DPB1, HLA-DQA1, HLA-DQB1, HLA-DRB1 and HLA-DRB345. It was also applied to the 16S rRNA gene. In the case of HLA-DQB1, the primers have been shown to work as intended. As is, a few assumptions were made (such as how many mismatches to be allowed between the primers and the sample DNA) that need to be tested and possibly refined.

25

30

Another improvement that can be made is the following: As is, the program works only with discrete signals, e.g. either there is a signal 'A' or there is not, either there is a signal 'G' or there is not and so on. A more precise approach would be to predict how strong the signals will be for each primer on each sequence. A rough estimate of the signal strength should be possible given some thermodynamic data about the primers, most notably their melting points. With this information, and knowing the concentration of DNA in the sample among other things, the proportion of primers on the chip that will actually react with the sample DNA should be possible to estimate. It would thus allow a rough estimation of what strength the different signals will have. It will not be very precise, and the estimate might possibly be off by a factor 2 or more, but it will still give some information about what signals to expect from the chip.

35

40

45

30

50

Given the melting points of the primers, the temperature at which the reaction on the chip is carried out could be optimised as well.

55

5

10

15

20

25

30

35

40

45

50

55

Since the sequences are known, it is possible to estimate the melting point of any primer to any sequence when there are a few mismatches. This could be done for all primers on all sequences, and a range of temperatures calculated. The actual temperature to use could then be chosen so as to be as optimal for as many primers on as many sequences as possible, instead of as now at a standard temperature.

Another possibility would be to try other heuristics to solve the resulting SCP. Even though CFT does give better results than the greedy algorithm, it is not by much. It could be that Lagrangian relaxation methods really are not suitable for unicost problems, but the only way to find out is to try heuristics based on other ideas. It might be possible to reduce the binary SCP-matrix as well, before applying any heuristic on it. Some rows in the matrix could end up the same, in which case one of them could be removed in order to reduce the number of rows and thus speed up computation. No figures of how many rows might be the same exist, but it could be worthwhile examining this possibility to reduce problem size.

The algorithm itself could be improved. The complexity of the redundancy-check phase can be slightly reduced by having a vector consisting of the sums of the rows in each node. For each child-node, the column to be removed is then subtracted from this vector of sums. This operation can be carried out in $O(m)$, and the final complexity will then be $O(m \times N(p, p))$ instead. For the greedy algorithm, another possible improvement is to check the primer set for redundancy each time a primer was added. The complexity for the greedy algorithm will be the same, as the check will take $O(m \times p)$ (i.e. same as each iteration in the greedy algorithm) each time (with the improvement just mentioned). The check could take longer, but that is unlikely as that would imply that one primer could make several other primers redundant. The main advantage is, of course, that no redundancy check with its rather high complexity is needed afterwards.

The most serious problem is the sheer size of the problems. For the 16S rRNA data set, around 300 MB is required just in order to store

5 all the primers and their signals. Add to that the fact the all primers need to
be traversed once for every iteration in the greedy algorithm, and the result
10 is that it will take quite some time as well. This also means that it is not
even feasible to use more elaborate algorithms such as the CFT algorithm
5 on the 16S rRNA data set, unless a much more powerful computer is
available. On the other hand, algorithm CFT would probably benefit quite a
15 lot from a parallel computer, since much computation could be carried out
as vector-operations. It should then be possible to spread out all
computations on several processors, thus reducing the time required. It
20 would also reduce the memory requirements on each processor (but then
parallel computers tend to have enough memory to store all necessary data
for this problem on each processor anyway). Even the greedy algorithm
would benefit from a parallel computer, as each processor can be charged
25 with the task of scoring only a subset of primers. It is not as critical in this
case, though, since the computation times are not very high when using the
greedy algorithm.

30 As is, this method is only capable of identifying known gene-
variants. If applied to a sample with a previously unknown variant, it is very
probable that this new variant will be falsely identified as one of the known
35 variants. It would be very advantageous if this method could be
augmented in some way to recognise this fact, and give a warning if there
could be an unknown variant in the sample. It could be done by giving a
warning when the signal pattern gained differs from the signal pattern from
40 any known variants, but this might not be enough. There is no guarantee
25 that the new variant could not differ in some place not affecting any of the
existing primers, which would lead to the new variant being
indistinguishable from any of the known variants. Some other way is
45 probably needed as well.

5

APPENDIX 1**Primer sequences for DBQ heterozygote typing**

Primers 'dqb1 -1' to 'dqb1 -8' placed in positions A3-A10.

Primers 'dqb1 -9' to 'dqb1 -18' placed in positions B2-B11.

Primers 'dqb1 -19' to 'dqb1 -30' placed in positions C1-C12.

Primers 'dqb1 -31' to 'dqb1 -42' placed in positions D1-D12.

Primers 'dqb1 -43' to 'dqb1 -54' placed in positions E1-E12.

Primers 'dqb1 -55' to 'dqb1 -66' placed in positions F1-F12.

Primers 'dqb1 -67' to 'dqb1 -76' placed in positions G2-G11.

Primers 'dqb1 -77' to 'dqb1 -84' placed in positions H3-H10.

10

15

20

25

30

35

40

45

50

55

dqb1-1 NH2 - TCC ATC ACA GGA GTC AGA AAG GGC T
 dqb1-2 NH2 - GTG TGC AGA CAC AAC TAC GAG GTG G
 dqb1-3 NH2 - GCG GTG ACG CTG CTG GGG CTG CCT G
 dqb1-4 NH2 - TAA TGA GGG GGG TGG ACA CAA CGC C
 dqb1-5 NH2 - GCG GTG ACG CCG CTG GGG CCG CCT G
 dqb1-6 NH2 - GGA CAT CCT GGA GGA GGA CCG GGC G
 dqb1-7 NH2 - GTG GTG ACG CCG CTG GGG CCG CCT G
 dqb1-8 NH2 - TCC GTC AAA GGA GTC AGA AAG GGC T
 dqb1-9 NH2 - GAT GTA TCT GGT CAC ACC CCG CAC G
 dqb1-10 NH2 - CCG AGT ACT GGA ATA GCC AGA AGG A
 dqb1-11 NH2 - GAT GTG TCT GGT CAC ACC CCG CAC G
 dqb1-12 NH2 - GGG TGG ACA CAA CGC CGG CTG TCT C
 dqb1-13 NH2 - GGG TGG ACA CAA CGC CGG TTG TCT C
 dqb1-14 NH2 - CTT CTG GCT ATT CCA GTA CTC GGC G
 dqb1-15 NH2 - TTC CGG GCG GTG ACG CTG CTG GGG C
 dqb1-16 NH2 - GCT TCG ACA GCG ACG TGG GGG TGT A
 dqb1-17 NH2 - GCT GTT CCA GTA CTC GGC GCT AGG C
 dqb1-18 NH2 - CTT CTG GCT GTT CCA GTA CTC GGC G
 dqb1-19 NH2 - ACC GTG TCC AAC TCC GCC CGG GTC C
 dqb1-20 NH2 - CAC AAC GCC GGT TGT CTC CTC CTG G
 dqb1-21 NH2 - CTC CTC CTG GTC ATT CCG AAA CCA C
 dqb1-22 NH2 - CCA GGA TCT GGA AAG TCC AGT CAC C
 dqb1-23 NH2 - GAG CGC GTG CGT CTT GTA ACC AGA T
 dqb1-24 NH2 - GAC ATC CTG GAG AGG AAA CGG GCG G
 dqb1-25 NH2 - AGA GAC TCT CCC GAG GAT TTC GTG T
 dqb1-26 NH2 - TAG TTG TGT CTG CAC ACC CTG TCC A
 dqb1-27 NH2 - ACG TAC TCC TCT CGG TTA TAG ATG T
 dqb1-28 NH2 - GCT TCG ACA GCG ACG TGG AGG TGT A
 dqb1-29 NH2 - TCC GTC CCA TTG GTG AAG TAG CAC A
 dqb1-30 NH2 - TGA TAA GGC CCA GCC CGA GGA AGA T
 dqb1-31 NH2 - GGG TGG ACA CAA CGC CAG TTG TCT C
 dqb1-32 NH2 - GGG TGG ACA CAA CGC CAG CTG TCT C
 dqb1-33 NH2 - GAC AGC GAC GTG GAG GTG TAC CGG G
 dqb1-34 NH2 - TCC GTC CCG TTG GTG AAG TAG CAC A
 dqb1-35 NH2 - GCA CGA CCT TGC AGC GGC GAC CCC A
 dqb1-36 NH2 - GAA CAG CCA GAA GGA AGT CCT GGA G
 dqb1-37 NH2 - CTT CTG GCT GTT CCA GTA CTC GGC A
 dqb1-38 NH2 - AAC GCC AGC TGT CTC TTC CTG GTC A
 dqb1-39 NH2 - GAG AGG ACC CGG GCG GAG TTG GAC A
 dqb1-40 NH2 - GCA GGC GGC CCC AGC GGC GTC ACC A
 dqb1-41 NH2 - GTC GCT GTC GAA GCG CAC GTC CTC C
 dqb1-42 NH2 - CTC TGT CCT GGA TGG GGT CGC CGC T
 dqb1-43 NH2 - ACG GGA CGG AGC GCG TGC GTT ATG T
 dqb1-44 NH2 - GAA GTA GCA CAT GCC CTT AAA CTG G
 dqb1-45 NH2 - TCG GTG GAC ACC GTA TGC AGA CAC A
 dqb1-46 NH2 - GGA M CGT GTA CCA GTT TAA GGG C
 dqb1-47 NH2 - ACG TAC TCT TCT CGG TTA TAG ATG T

5

10

15

20

25

30

35

dqb1-48 NH2 - GAG AGG ACC CGA GCG GAG TTG GAC A
dqb1-49 NH2 - ACC CCA GCC TCC AGA GCC CCA TCA C
dqb1-50 NH2 - CAA CGG GAC GGA GCG CGT GCG GGG T
dqb1-51 NH2 - ACA TCT ATA ACC GAG AGG AGT ACG C
dqb1-52 NH2 - GAA CAG CCA GAA GGA CAT CCT GGA G
dqb1-53 NH2 - CCT TCT GGC TAT TCC AGT ACT CGG C
dqb1-54 NH2 - TTA AGG CCA TGT GCT ACT TCA CCA A
dqb1-55 NH2 - TTC AGA TTG AGC CCG CCA CTC CAC G
dqb1-56 NH2 - ATC TGG TCA CAA GAC GCA CGC GCT C
dqb1-57 NH2 - AGT AGC ACA GGC CCT TAA ACT GGT A
dqb1-58 NH2 - ATG TAT CTG GTC ACA CCC CGC ACG A
dqb1-59 NH2 - ATC TGG TCA CAT AAC GCA CGC GCT C
dqb1-60 NH2 - ATC AAA GTC CAG TGG M CGG AAT G
dqb1-61 NH2 - ACG TGG GGG TGT ATC GGG TGG TGA C
dqb1-62 NH2 - ATC AAA GTC CGG TGG M CGG AAT G
dqb1-63 NH2 - GTA TCT GGT CAC ACC CCG CAC GAG C
dqb1-64 NH2 - CGC TGT CGA AGC GCA CGT CCT CCT C
dqb1-65 NH2 - GGA M CGT GTT CCA GTT TAA GGG C
dqb1-66 NH2 - TGT GGG CTC CAC TCT CCT CTG CAA G
dqb1-67 NH2 - ACG TCC TCC TCT CGG TTA TAG ATG T
dqb1-68 NH2 - TTG CAG CGG CGA CCC CAT CCA GGA C
dqb1-69 NH2 - GAA GTA GCA CAG GCC CTT AAA CTG G
dqb1-70 N H2 - GAA GTA GCA CAT GGC CTT AAA CTG G
dqb1-71 NH2 - TCG ACA GCG ACG TGG GGG TGT ACC G
dqb1-72 NH2 - TCG ACA GCG ACG TGG GGG AGT TCC G
dqb1-73 NH2 - TGT GGG CTC CAC TCG CCG CTG CAA G
dqb1-74 NH2 - CGG CGT CAG GCC GCC CCT GCG GGG T
dqb1-75 N H2 - TCG ACA GCG ACG TGG AGG TGT ACC G
dqb1-76 NH2 - GCG TTG GAG GCT TCG TGC TGG GGC T
dqb1-77 NH2 - CGG TGA CCC CGC AGG GGC GGC CTG A
dqb1-78 NH2 - ATG GGA CGG AGC GCG TGC GTT ATG T
dqb1-79 NH2 - CGG TGA CGC CGC TGG GGC GGC TTG A
dqb1-80 NH2 - ACG GGA CGG AGC GCG TGC GTC TTG T
dqb1-81 NH2 - TGA TAA GGC CAA GCC CAA GGA AGA T
dqb1-82 NH2 - GAG ACT CTC CCG AGG ATT TCG TGT A
dqb1-83 NH2 - CGT CGC TGT CGA AGC GCA CGT CCT C
dqb1-84 NH2 - GAC TCT CCC GAG GAT TTC GTG TAC C

40 APPENDIX 2Homozygotes

(From CFT if available, otherwise greedy algorithm).

DPA1

45 TTTTTTTTTTGGCCAGGGCACAG
TTTTTTTTTTAAGGAAAAGGCTC
TTTTTTTTTTTGGATCTGGACAA
TTTTTTTTTTCTGGCCAGCTCC
TTTTTTTTTTGTACAGACCCA
50 TTTTTTTTTTAGGGGACCCTGTG
TTTTTTTTTTGGCGGACCATGTG
TTTTTTTTTTCTGCTCATCTTCA
TTTTTTTTTTGTCAACTTATGCC
55 TTTTTTTTTTCAGGCCGCCAAT

5

10

15

20

25

30

35

40

45

50

55

DPB1

TTTTTTTTTTCAACCGGGAGGAG
TTTTTTTTTTGGCCTGACGAGGA
TTTTTTTTTTCAACCTGGAGGAG
TTTTTTTTTTCCAGTACTCCTC
TTTTTTTTTTGCCGTAACGGT
TTTTTTTTTTGGGGCGCCTGA
TTTTTTTTTTGCGCGTACTCCTC
TTTTTTTTTTGGACAGGAGGAA
TTTTTTTTTTACAGGAGGAGCA
TTTTTTTTTTGCTCCTCCTGT
TTTTTTTTTTGGCAATGCCCGCT
TTTTTTTTTTGGCACTGCCCGCT
TTTTTTTTTTAGAGAATTACGTG
TTTTTTTTTTCCAGAGAATTAC
TTTTTTTTTTAACTACGAGCTGG
TTTTTTTTTTGGTCATGGGCCCG
TTTTTTTTTTGACCGTGACGCG
TTTTTTTTTTACACGTAATTCT
TTTTTTTTTTGTAAGTGGTACAC
TTTTTTTTTTCTGACGAGGAGTA
TTTTTTTTTTTACCTTTCCAG
TTTTTTTTTTTCTGGAAAAGGTA
TTTTTTTTTTGAGAATTACCTTT
TTTTTTTTTTTGCCTGACGAGGAG
TTTTTTTTTTTACTGGTGCACGTA
TTTTTTTTTTTCTCCAGGATGT
TTTTTTTTTTTCGGGAGGAGCTCG
TTTTTTTTTTTAGCCAGAAGGACA
TTTTTTTTTTTCAAGCCAGAAGGAC
TTTTTTTTTTTAGTGCCGACAGG
TTTTTTTTTTTATTGCCGACAGG
TTTTTTTTTTTCTGCAGCGCCGA
TTTTTTTTTTTAGAGAATTACCTT
TTTTTTTTTTTGGACTCGGCGCTG
TTTTTTTTTTTACTACGAGCTGGG
TTTTTTTTTTTGCTTCGTGCTGGG
TTTTTTTTTTGTCCCTGGTACAC
TTTTTTTTTTGCGCTGCAGGGTC

DQA1

TTTTTTTTTTTACATCCTCATCTG
TTTTTTTTTTTACACCCTCATCTG
TTTTTTTTTTTCAAGTTTACACCA
TTTTTTTTTTTCAGCCACAATGTC
TTTTTTTTTTTCCAAGTCTCCCG
TTTTTTTTTTTCGGGAGACTTGG
TTTTTTTTTTTAATTCATGGCTGT
TTTTTTTTTTTACAATCCCAGGGC
TTTTTTTTTTTACAACCCAGGGC
TTTTTTTTTTTGTGGGCATTGTGG
TTTTTTTTTTTCCAACACCCTCAT
TTTTTTTTTTTGGCCACAGACAA
TTTTTTTTTTTCATGGGCATTGTG
TTTTTTTTTTTGGCCTGGATGAGC
TTTTTTTTTTTAGGCTCATCCAGG
TTTTTTTTTTTCAACACCCTCATT
TTTTTTTTTTTAGCACTGGGGACT
TTTTTTTTTTTAAGGGCCATTGTG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTAAATTCATGGGTG
TTTTTTTTTACCATAAGAGGC
TTTTTTTTTACCACAAGAGGC
TTTTTTTTTACCGTAAGAGGC
TTTTTTTTTTCCTCCCTTCTG
TTTTTTTTTAACTCTCCTCAG
TTTTTTTTTAAATCTCATCAG
TTTTTTTTTCTCCTCCCTTCTG

DQB1

TTTTTTTTTATCTTGCAAGGA
TTTTTTTTTCTCTCCAGGATG
TTTTTTTTTGGGTACCGCCCG
TTTTTTTTTGGGAGTCCGGGC
TTTTTTTTTCGCTCGGGTCTC
TTTTTTTTTCCAGTACTCGGCG
TTTTTTTTTCTGGGGCCGCCTG
TTTTTTTTTATGTCTACACCTG
TTTTTTTTTAAAGGGCTTCTGC
TTTTTTTTTAGCATCACCAGGA
TTTTTTTTTGCCAGGAGGAGAC
TTTTTTTTTACCAGGAGGAGAC
TTTTTTTTTGGTTTCGGAATGA
TTTTTTTTTGGGTGTATCGGGT
TTTTTTTTTGTCTGAAAGGGCT
TTTTTTTTTGGTTTCGGAATG
TTTTTTTTTCCAGTACTCGGCA
TTTTTTTTTAGCGCACGATCTC
TTTTTTTTTGTCTCTTCTGGT
TTTTTTTTTCGTCAAGCCGCC
TTTTTTTTTGCGTCAAGCCGCC
TTTTTTTTTCAAGGTCGTGCGG
TTTTTTTTTCGGTTATAGATGT
TTTTTTTTTGTAAACGACAC
TTTTTTTTTGTATGCAGACACA
TTTTTTTTTCACACCCCGCACG
TTTTTTTTTACACCCCGCACGC

DRB1

TTTTTTTTTGCAAGTCTCCTC
TTTTTTTTTCTCTCCGGT
TTTTTTTTTCCACAACCCGGTA
TTTTTTTTTGGCCAGGTGGACA
TTTTTTTTTGCAGTCTCTGGAG
TTTTTTTTTCAGCCAGAAGGAC
TTTTTTTTTGACTCGCCTCTGC
TTTTTTTTTCCAGGACTCGGC
TTTTTTTTTGAAATAACACTCA
TTTTTTTTTGGAGGACAGGCG
TTTTTTTTTACGTGGTGGGGTG
TTTTTTTTTACTCCAAGAAAC
TTTTTTTTTACGGTGTCCACCT
TTTTTTTTTGGAGAGGTTTACA
TTTTTTTTTCCAGTACTCGGCA
TTTTTTTTTGGAGTACTCTACG
TTTTTTTTTGTGTAAACCTCTC
TTTTTTTTTTCGGTGCAGCGGCG
TTTTTTTTTGGAGGAGTTCCTG
TTTTTTTTTGGAAAGACGAGCG
TTTTTTTTTTCAGGAGGTTGTGG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTGACAGGCGCGCCG
TTTTTTTTTTCCGTTTCAGGAACC
TTTTTTTTTTGGAATCCTCTTGG
TTTTTTTTTTGCCACAAGAAACG
TTTTTTTTTTACGTTTCTTGGAG
TTTTTTTTTTTCGGACTCCTCTTG
TTTTTTTTTTTACGGGTGAGTGT
TTTTTTTTTTTCCAGGAGGAGTTC
TTTTTTTTTTTGTAAATTGTCCACC
TTTTTTTTTTTCGTAGCGCGCGT
TTTTTTTTTTTAAAGATGCATCTAT
TTTTTTTTTTTACGTCTGAGTGT
TTTTTTTTTTTCCAGTACTCAGCA
TTTTTTTTTTTCGTAGCGCGCGTA
TTTTTTTTTTTATCTCTCCACAAC
TTTTTTTTTTTGAGCTCCTCCTGG
TTTTTTTTTTTAACCAGGAGGAGT
TTTTTTTTTTTAGGGCCCCGCTGT
TTTTTTTTTTTGGAGAGCTTCACA
TTTTTTTTTTTGGAGAGATTACA
TTTTTTTTTTTACCGCCCGGTA
TTTTTTTTTTTAACTACCGGGTTG
TTTTTTTTTTTCCAGTACTGGGCA
DRB345
TTTTTTTTTTTGTATCTGTCCAGG
TTTTTTTTTTTGACTGGGGTGGTG
TTTTTTTTTTTCTGTCAAGCGCA
TTTTTTTTTTTGTGTAACCTCTC
TTTTTTTTTTTCTGTGAAGCTCTC
TTTTTTTTTTTCACCAGGGCCCGC
TTTTTTTTTTTGGCCAGGTGGACA
TTTTTTTTTTTGCGGTTCCTGGAG
TTTTTTTTTTTCGAAGCGCGCGT
TTTTTTTTTTTAACCAGGAGGAG
TTTTTTTTTTTACGTGGTCGGGTG
TTTTTTTTTTTAGGGCCCCGCTGT
TTTTTTTTTTTGGGCCCCGCTGTC
TTTTTTTTTTTAACTACGGAGTTG
TTTTTTTTTTTGGGGCCGGGCTGT
TTTTTTTTTTTGACCATGTTTCTT
TTTTTTTTTTTCTGTGCAGGAACC
TTTTTTTTTTTGGCCGGGCTGTC
TTTTTTTTTTTACATCCTGGAAGA
TTTTTTTTTTTCTCACGAGTCCTG
HLA-A
TTTTTTTTTTTCAGTCTGTGAGT
TTTTTTTTTTTAGACGCATATGAC
TTTTTTTTTTTGGACGCATATGAC
TTTTTTTTTTTGGTCGCCAGGTCC
TTTTTTTTTTTCCGCAGGCTCTCT
TTTTTTTTTTTCTCTCTCCACAT
TTTTTTTTTTTCCGAACCCTCGTC
TTTTTTTTTTTATTTCTCCACATC
TTTTTTTTTTTGGCGGACATGGCG
TTTTTTTTTTTCCAGAGCGAGGAC
TTTTTTTTTTTCACCACATCCG
TTTTTTTTTTTGGGAGCCTGCCCA
TTTTTTTTTTTGATGTGGAGGAG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTGGAGGAGGAACAG
TTTTTTTTTTAGTCATATGCGTC
TTTTTTTTTTGGTCTGCCCGAGC
TTTTTTTTTTAAACCTGCCATGT
TTTTTTTTTTCCGGGACACGGAA
TTTTTTTTTTGTCCTGGGGGGG
TTTTTTTTTTCCGCTGCCAGGTC
TTTTTTTTTTATGCGTCTGGGG
TTTTTTTTTTATGCGTCTGGGG
TTTTTTTTTTGAGAAGAGATAC
TTTTTTTTTTGGGAGCCGCCCA
TTTTTTTTTTCCGCAGGTTCTCT
TTTTTTTTTTGCGCAGGTCCTCT
TTTTTTTTTTGGGCGGGCTCTCA
TTTTTTTTTTCCAGGACACGGAG
TTTTTTTTTTCCGGCAGTGGAGA
TTTTTTTTTTAGGAGACAGGGAA
TTTTTTTTTTGTCAATCTGTGAG
TTTTTTTTTTAGAAAGTGGGTGGC
TTTTTTTTTTCAAGTAGGCTCTC
TTTTTTTTTTCCGACGCCCCCAA
TTTTTTTTTTCAATCTGTGAGT
TTTTTTTTTTGAAGGCCAGTC
TTTTTTTTTTTCGTCTGAAGCGTC
TTTTTTTTTTAACCAGAGCGAGG
TTTTTTTTTTGACGGTCATGGC
TTTTTTTTTTGGACCTGGCGAC
TTTTTTTTTTGAGAGCCGCCCA
TTTTTTTTTTTCATATTCGGTGT
TTTTTTTTTTGGGAGACACGGAA
TTTTTTTTTTGTCCACTCGGTCA
TTTTTTTTTTCCGTGTCTCCCGG
TTTTTTTTTTGCTGCCACGTGGG
TTTTTTTTTTTCGAACTGCGTGTCT
TTTTTTTTTTGGTAGGCTCTCAA
TTTTTTTTTTAGGTCCACTCGGT
TTTTTTTTTTGTCCTGGGGGGGT
TTTTTTTTTTGCTGCTCCGCCGC
TTTTTTTTTTGGGGCGCCATGAC
TTTTTTTTTTGCGCGATCCGCAG
TTTTTTTTTTGCACATGGCAGGT
TTTTTTTTTTAGGAGAAGAGATA
TTTTTTTTTTAGGAGCAGAGATA
TTTTTTTTTTCCACTCCACGCAC
TTTTTTTTTTCCCGTCCACGCAC
TTTTTTTTTTACGTGCCATCCA
TTTTTTTTTTCCCGGCCCGGCAG
TTTTTTTTTTACGTCCGAGCCA
TTTTTTTTTTACGTCCGAGCCAT
TTTTTTTTTTACGTGGCAGCCAT
TTTTTTTTTTATCCAGAGGATGT
TTTTTTTTTTTCGAGCTCCGTGTC
TTTTTTTTTTACCAGAGCGAGGA
TTTTTTTTTTATGAACAGCACGC
TTTTTTTTTTTCACACCCTCCAG
TTTTTTTTTTCTACGTGGACAAC

5

10

15

20

25

30

35

40

45

50

55

HLA-B

TTTTTTTTTTGGATGGCGCCCGG
TTTTTTTTTTTCGGCTCAGATCTC
TTTTTTTTTTTCGGGGCGCCGTG
TTTTTTTTTTCTCCACTGCTCCG
TTTTTTTTTTGTGTTGGTCTTG
TTTTTTTTTTGGGTATGACCACT
TTTTTTTTTTTCCAGGTGATGTA
TTTTTTTTTTGTCTGCTCCGCC
TTTTTTTTTTGTAGTAGCGGAG
TTTTTTTTTTGCTCAGGTCTCC
TTTTTTTTTTACCAACACACAGA
TTTTTTTTTTCCGTCGTAGCGGT
TTTTTTTTTTGTGAGCCTGCGGA
TTTTTTTTTTACATCATCCAGAG
TTTTTTTTTTGGTTCTCTCGGTA
TTTTTTTTTTGATGTGTCTCTC
TTTTTTTTTTGCGCCATGACCAG
TTTTTTTTTTGGCGTCTGGTCA
TTTTTTTTTTAGGAGGACCTGAG
TTTTTTTTTTGCGCCAGGCACAG
TTTTTTTTTTAGGAGGGGCGGA
TTTTTTTTTTCCGCTGCTCCGCC
TTTTTTTTTTACACCATCCAGAG
TTTTTTTTTTACACACAGATCTAC
TTTTTTTTTTGGGCATGACCACT
TTTTTTTTTTACACACAGATCTCC
TTTTTTTTTTGCGAGTGCCTGGA
TTTTTTTTTTGGTACCGCGGA
TTTTTTTTTTCCCTGTGCGTGGAG
TTTTTTTTTTAGACACAGATCTT
TTTTTTTTTTTACGCGACGCCACG
TTTTTTTTTTTCGGGCCGGGACAC
TTTTTTTTTTTCCGTCCCAATAC
TTTTTTTTTTTGGGCATAACCACT
TTTTTTTTTTTGCCCGCTTCATC
TTTTTTTTTTTACGGAGCGCAGGT
TTTTTTTTTTTCGTCCACGCACAG
TTTTTTTTTTTGAGTCCGAGAGAG
TTTTTTTTTTTGACACAGATCTCC
TTTTTTTTTTTAACCACTTAGCC
TTTTTTTTTTTAGGCGTGTGGT
TTTTTTTTTTTGACCTGCTCCGC
TTTTTTTTTTTGGGGCTCCGCAGA
TTTTTTTTTTTCCGTCCCAATAC
TTTTTTTTTTTGGGGTCCAGCGG
TTTTTTTTTTTAGGGCCAGGGCTC
TTTTTTTTTTATCCTCTGGAGGG
TTTTTTTTTTTGGCAGACGATGTA
TTTTTTTTTTTAGGCGGAGCAGGA
TTTTTTTTTTTCACTGCTCCGCC
TTTTTTTTTTTATCTGCGGAGCCA
TTTTTTTTTTTCGGAGCTGTGGTC
TTTTTTTTTTTCGACCACAGTCTC
TTTTTTTTTTTGAAGAGTTCAGGT
TTTTTTTTTTTCATGTGCGAGCCA
TTTTTTTTTTTCTGGGCTGGGTCC
TTTTTTTTTTTCAACACACAGACT
TTTTTTTTTTTGGCGGAGCAGGA

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTATGACCAGGACG
TTTTTTTTTTTCCACTGCTCCGCC
TTTTTTTTTTTATGACCAGGACGC
TTTTTTTTTTTGGAGGGGCGGAG
TTTTTTTTTTTGCGTGACGGGC
TTTTTTTTTTTAGATCTGTATCTC
TTTTTTTTTTTGC GGTCATGGCG
TTTTTTTTTTTCCGGGACATGGCG
TTTTTTTTTTTCCACAGCTGTCCA
TTTTTTTTTTTCCGGACATGGCGG
TTTTTTTTTTTCCCGTCCACGCAC
TTTTTTTTTTTGAAGTGGGAGCCG
TTTTTTTTTTTCCCAATCCACC
TTTTTTTTTTTCCACAGATGGGGA
TTTTTTTTTTTCCCAAGTCCACC
TTTTTTTTTTTGAGATCTGAGCCG
TTTTTTTTTTTCCACGCACTCGC
TTTTTTTTTTTGACAGCGACGCCA
TTTTTTTTTTTCGCCGCGGACACC
TTTTTTTTTTGTAGGAGGAAGAG
TTTTTTTTTTCTTTCCACCTGA
TTTTTTTTTTTCACTCGCAGCCA
TTTTTTTTTTTCAGGTCGCAGCCA
TTTTTTTTTTTCGTAGCCCACTGC
TTTTTTTTTTTATCCAGGTGATGT
TTTTTTTTTTTCCCAATCCACCG
TTTTTTTTTTTGGGCGCTTCCTCC
TTTTTTTTTTTCCCGCTTCATCGC
TTTTTTTTTTTCCCGCTTCATCG
TTTTTTTTTTTACACAGACTTAC
TTTTTTTTTTTAGGACGGTTCGGG
TTTTTTTTTTTCCCGAACCCTCC
TTTTTTTTTTTGAGCTCTTCCTCC
TTTTTTTTTTTGCTCCCGAGAGCA
TTTTTTTTTTTACTCCATGAGGCA
TTTTTTTTTTTGCTGTGGTGGTGC
TTTTTTTTTTTGTCCAGAAGGC
TTTTTTTTTTTGCCGCGGAGGA
TTTTTTTTTTTGCCGCGGACAAGG
TTTTTTTTTTTCCGCCTTGTCGCG
TTTTTTTTTTTCGGGTACCACCAG

HLA-C

TTTTTTTTTTTGAGCTGGGAGCC
TTTTTTTTTTTGGTGCAGGGCTCC
TTTTTTTTTTTGGGTGCAGGGCTC
TTTTTTTTTTTGAGGCGGAGCAGC
TTTTTTTTTTTACGGCGGAGCAGC
TTTTTTTTTTTGCGGCGGAGCAGC
TTTTTTTTTTTAGCGCGCGGAACC
TTTTTTTTTTTCGGCCCAGGTCTC
TTTTTTTTTTTGGCTCCAGCTC
TTTTTTTTTTTGCGCGCGGAACCC
TTTTTTTTTTTACGGCTTCATCT
TTTTTTTTTTTGGTTCGGGGCTCC
TTTTTTTTTTTACTCCAGGCACAG
TTTTTTTTTTTGGAGCAGGAGGG
TTTTTTTTTTTGCGCGCAGAACCC
TTTTTTTTTTTGAGTCTCTCATC
TTTTTTTTTTTCCTGCAGCCCTC

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTCCGCCGTGTCCGC
TTTTTTTTTCCGCTGTGTCCGC
TTTTTTTTTCCAGAATATGTA
TTTTTTTTTCCGGGAGCCCGC
TTTTTTTTTGCCGTCGTAGGCG
TTTTTTTTTCCGCCAGGCACAG
TTTTTTTTTGCGCCAGGCACAG
TTTTTTTTTGTAGCCGCGCAGG
TTTTTTTTTGCTGGACGCAGCC
TTTTTTTTTCCAGTGGATGTA
TTTTTTTTTCCACGCACAGGC
TTTTTTTTTGCCGTGTCCGCAG
TTTTTTTTTGAGGGGAGCCCGC
TTTTTTTTTCGTGTCCCAGCCT
TTTTTTTTTGGCATGACCAGTT
TTTTTTTTTGGTATGACCAGTT
TTTTTTTTTGACAACCAGGACA
TTTTTTTTTGAATATGTATGGC
TTTTTTTTTGACAGCCAGGACA
TTTTTTTTTCTGGCTGTCTTGG
TTTTTTTTTCTCCTAGGACAGC
TTTTTTTTTAGGGCCAGGGCTC
TTTTTTTTTATAACCAAGTTCC
TTTTTTTTTCATAGGAGGAAGA
TTTTTTTTTGTGGAGACCAGG
TTTTTTTTTGCTCTTCTCCAG
TTTTTTTTTGAAGAATGGGAAG
TTTTTTTTTGCGGAACTGCG

16S rRNA

TTTTTTTTTAGCCGCCTGCGT
TTTTTTTTTGCCCGCAAGGCTG
TTTTTTTTTGAAGTCCGTTGA
TTTTTTTTTAGACTGCCGCTGA
TTTTTTTTTATTCCGAATTA
TTTTTTTTTGCACCCCTTGT
TTTTTTTTTCGCGAGGTTGAGC
TTTTTTTTTACCCCCATTGT
TTTTTTTTTCATTTGATACTGG
TTTTTTTTTGTGTGCCTAATAC
TTTTTTTTTACGACTTAACCC
TTTTTTTTTCCCGCCCTTGTA
TTTTTTTTTGGGCAAAGTGGAG
TTTTTTTTTGATTTGATCCTGG
TTTTTTTTTGACTCCCGAAGG
TTTTTTTTTGAAGTCGTAGCAA
TTTTTTTTTCGCTGCAGAGATG
TTTTTTTTTACCCTACCTACT
TTTTTTTTTGAGGACCTTCGGG
TTTTTTTTTAAGGGCCATTACC
TTTTTTTTTGATAAACGCTGGC
TTTTTTTTTGAAGTACTACTCC
TTTTTTTTTACATCCGGTGTTA
TTTTTTTTTATCGCAGGCCTTG
TTTTTTTTTCACCAAGTCGCT
TTTTTTTTTCCCTCCTTCGG
TTTTTTTTTTAAACGCTGGC
TTTTTTTTTCGAAACCGCAAGG
TTTTTTTTTGCAAGCGTCTCC
TTTTTTTTTACCAAGGACGTTT

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTCTAATACCCGGAG
TTTTTTTTTTTACTTTCAGTGGGG
TTTTTTTTTTTCTGCGTGAAGTCG
TTTTTTTTTTTAATAGCCCACCAA
TTTTTTTTTTTAACGGAAACGGGG
TTTTTTTTTTTGGATTGCACTCTG
TTTTTTTTTTTAGCCTTGGGGGAG
TTTTTTTTTTTCGCCGATGGCTG
TTTTTTTTTTTGCATAAGGGGCAT
TTTTTTTTTTTACCACATCTCTG
TTTTTTTTTTTGTACCGCGAGGA
TTTTTTTTTTTGGCTTTCAGAGAT
TTTTTTTTTTTCGCTGCTTCGCTG
TTTTTTTTTTTAGCGCTACCTTG
TTTTTTTTTTTGCACCACCTGTCA
TTTTTTTTTTTGAGTTTAACTT
TTTTTTTTTTTCTAATACGGGATA
TTTTTTTTTTTAGGAGAAAGCTTG
TTTTTTTTTTTAAGAGATTAGC
TTTTTTTTTTTGTAGCATCTGAT
TTTTTTTTTTTAGGCTTCCCCCA
TTTTTTTTTTTAGAAGTAGCTTGC
TTTTTTTTTTTCGCGTATCATCG
TTTTTTTTTTTCAGAGATTAGC
TTTTTTTTTTTCCGAAAGCGTGG
TTTTTTTTTTTACAACCGGAAGC
TTTTTTTTTTTGTCTATGGCTCAG
TTTTTTTTTTTCGTAGGCTTGGTG
TTTTTTTTTTTGTGGAATCCACG
TTTTTTTTTTTACGGTTCCCGAAG
TTTTTTTTTTTAACTCGAGTGCCT
TTTTTTTTTTTGATGTGCTATTA
TTTTTTTTTTTAAGCAGGGAGGAA
TTTTTTTTTTTCTGCTGCAGTGAA
TTTTTTTTTTTGGGATTAGCTC
TTTTTTTTTTTCCTTTGATACTGG
TTTTTTTTTTTGGACGCTAGCGGC
TTTTTTTTTTTGTACTACTCCAC
TTTTTTTTTTTCGCGATCTCTAGC
TTTTTTTTTTTAGGCCGTCCCCC
TTTTTTTTTTTACGGTTGCATCG
TTTTTTTTTTTGCCCGTCAAGCCA
TTTTTTTTTTTAGTCCCGCCATT
TTTTTTTTTTCTAGCCGTAAGGG
TTTTTTTTTTTGTCCCTCGGGGG
TTTTTTTTTTTAACCAACTCCCAT
TTTTTTTTTTTACTGTGGGTAATA
TTTTTTTTTTTCTGAAAGATGGCG
TTTTTTTTTTTCGAAAGCCAGGGG
TTTTTTTTTTTGTCCGGAATCTG
TTTTTTTTTTTCAGAAAGTGGGTAG
TTTTTTTTTTTCAGTCCTCATGG
TTTTTTTTTTTGAAAGAAGCTTGC
TTTTTTTTTTTGACCACCTGTCAC
TTTTTTTTTTTGGAAGTGCAT
TTTTTTTTTTTACAGTTCCCGAAG
TTTTTTTTTTTCTCATATCTCTAC
TTTTTTTTTTTCAGTGAGGAAG
TTTTTTTTTTTACTGTGAGGAAGG
TTTTTTTTTTTCCAGCCCGTAAG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTTCGTAGCCTTGGTG
TTTTTTTTTTTATGATGCGTAGCC
TTTTTTTTTTTAGGCAGTGGCTCA
TTTTTTTTTTTCAGGACTTAACCC
TTTTTTTTTTTGGCCAGGCCGTAA
TTTTTTTTTTTCCAACCTCGTGC
TTTTTTTTTTTGAAGCGTGTGTGA
TTTTTTTTTTTCTCCCCGAAGGT
TTTTTTTTTTTATGGGAGTTTGT
TTTTTTTTTTTGTGTGCCGTTACC
TTTTTTTTTTTAGCAGTGAGGAAT
TTTTTTTTTTTGCCCGGTAACT
TTTTTTTTTTTGCACCGGCAGTCA
TTTTTTTTTTTGGACCTTCCTCTC
TTTTTTTTTTTACCTAGGTGGGAT
TTTTTTTTTTTAATAGCTAATACC
TTTTTTTTTTTGCCATATCTCTAC
TTTTTTTTTTTGCCGTTGGGGTAA
TTTTTTTTTTTACCCACCTTCG
TTTTTTTTTTTCAAGGCCTGGGAA
TTTTTTTTTTTCAACCCTGGTGGC
TTTTTTTTTTTCTAGTCATCCAGT
TTTTTTTTTTTGGCTGCTGCCCTCC
TTTTTTTTTTTCCCAGAGCTCAAC
TTTTTTTTTTTGAAGCTTGATCC
TTTTTTTTTTTAACACGCTGGCAA
TTTTTTTTTTTGAGCTTGCTCCCC
TTTTTTTTTTTATTTAGTTGAGCA
TTTTTTTTTTTCGACTTAGGCTCA
TTTTTTTTTTTGATGTGCTATT
TTTTTTTTTTTCTTAGGTGCCAGC
TTTTTTTTTTTGGCTACAGATCGT
TTTTTTTTTTTAACTTGCGTGCAT
TTTTTTTTTTTGCGATTACGTCAA
TTTTTTTTTTTGGACGTTGGCGGC
TTTTTTTTTTTGGTGGAGCATGT
TTTTTTTTTTTATAAACCATGCGG
TTTTTTTTTTTAAGAAGTGGGTAG
TTTTTTTTTTTAACAAGCTAATCC
TTTTTTTTTTTCCATGGTTTGAC
TTTTTTTTTTTAGTAACTGCCGGT
TTTTTTTTTTTCAAAGGGGGCGT
TTTTTTTTTTTGGCGCTTGCCTC
TTTTTTTTTTTGCTACCTACGTGC
TTTTTTTTTTTGCGAGGTGGAGC
TTTTTTTTTTTCGCGAGGTGGAGC
TTTTTTTTTTTGCTACCTACTTCT
TTTTTTTTTTTAAACATACAA
TTTTTTTTTTTGTGTGAAATGT
TTTTTTTTTTTCGTAAACTCAA
TTTTTTTTTTTCAAGGGGCAAGT
TTTTTTTTTTTCCAACCTTGC GG
TTTTTTTTTTTGGAGGAACGTGGG
TTTTTTTTTTTATAAGCCTCTCAG
TTTTTTTTTTTATGCTAATCCCA
TTTTTTTTTTTGATGCTAATCCCA
TTTTTTTTTTTGCCAGTGTTGCTC
TTTTTTTTTTGTAAAGGTGGGGA
TTTTTTTTTTTAAACACCGGCC
TTTTTTTTTTTCCAAGGCGGTGAT

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTGCTACGGCTAACT
TTTTTTTTTTAGTCGAGCACTCT
TTTTTTTTTTAAGGGTAGCTAAT
TTTTTTTTTTGTCACAGTACGAG
5 TTTTTTTTTTGAAAGCACTTTA
TTTTTTTTTTGGCGCAAGGCTTA
TTTTTTTTTTGCCTAGGTGGGAT
TTTTTTTTTTGTCCCCACGTTCC
TTTTTTTTTTGGCCACAAGGGGA
10 TTTTTTTTTTCTAGCTGTAGGGA
TTTTTTTTTTGTGGGCAGCAAGC
TTTTTTTTTTTCGAAAGATTAAA
TTTTTTTTTTGGAGTATGGTCGC
TTTTTTTTTTTCGAGATGTGAAAG
15 TTTTTTTTTTGGGCAGGCTAGAG
TTTTTTTTTTTACCTCCTGAGCCA
TTTTTTTTTTTCCACCGCTACAC
TTTTTTTTTTTCAGTCTTGCG
20 TTTTTTTTTTCTTGACGGGCGGT
TTTTTTTTTTTACGGTAAAAGATG
TTTTTTTTTTTCACCCCTTGCGG
TTTTTTTTTTTAACCAGAAAGCC
TTTTTTTTTTCAACCAGAAAGCC
25 TTTTTTTTTTGTGTCAAAGGCAG
TTTTTTTTTTTAAGTCCGATTG
TTTTTTTTTTGCGACATGCTGAT
TTTTTTTTTTATCAGCCTGCCGC
TTTTTTTTTTGTCGGTAGGGTAA
30 TTTTTTTTTTGTGGGTGGGGTAA
TTTTTTTTTTCAACTCATAAGGG
TTTTTTTTTTTCACTGCTTAAA
TTTTTTTTTTTCCGAGTCCCACC
TTTTTTTTTTCTAGTCATAAGGG
35 TTTTTTTTTTCACTGATTGACG
TTTTTTTTTTGGCCACACAGGGA
TTTTTTTTTTTCCCCCATTGT
TTTTTTTTTTTGACCAGAAAGGG
40 TTTTTTTTTTACACTGGGGGATA
TTTTTTTTTTTCAGCCGCCCTCG
TTTTTTTTTTGTCGCCAGCTCGT
TTTTTTTTTTCTCATATGAATTG
TTTTTTTTTTGTAAAGGGAGCG
TTTTTTTTTTTCGTAAAGGGAGCG
45 TTTTTTTTTTGGCGGCTCCCTCC
TTTTTTTTTTTCAGATGTTCCCTCC
TTTTTTTTTTGTCTCAGCACACG
TTTTTTTTTTTCAGCCGCCCTACG
TTTTTTTTTTGTGCTAATACC
TTTTTTTTTTCTTGGAAGTGCAT
50 TTTTTTTTTTAGTACTCACCCGT
TTTTTTTTTTATTGCTCCATCAG
TTTTTTTTTTGATCCTGAGCCA
TTTTTTTTTTTAGCAAGTAGAACG
TTTTTTTTTTTGCAAGTAGAACG
55 TTTTTTTTTTGATAACCGCAAGG
TTTTTTTTTTTGCAAGCGTTTCC
TTTTTTTTTTGAATACCTCCTTT
TTTTTTTTTTTACAGAGCTTTACA
60 TTTTTTTTTTGTCTTCGGGAG
TTTTTTTTTTTAGGCGGCTTGCTG

5

Heterozygotes

From CFT if available, otherwise greedy algorithm.

10

5 DPA1

15

20

25

30

```
TTTTTTTTTTGCCCAGGGCACAG
TTTTTTTTTTCTGTTGTTCTATG
TTTTTTTTTTAAGGAAAAGGCTC
TTTTTTTTTTATGAAGATGAGCA
TTTTTTTTTTCACCTCAGTGAC
TTTTTTTTTTGTCAACTTATGCC
TTTTTTTTTTGCAGGAAGAGGCT
TTTTTTTTTTGTACAGACGC
TTTTTTTTTTCGGTCTCCTTCTT
TTTTTTTTTTGCAATGGGGAGCC
TTTTTTTTTTGGATCTGGATAA
TTTTTTTTTTGATGAAGATGAG
TTTTTTTTTTGTTGTACAGAC
TTTTTTTTTTCGTTGTACAGAC
TTTTTTTTTTCAGGCCGCCAA
TTTTTTTTTTCAGGCCACCAA
TTTTTTTTTTATGTGGATCTGGA
TTTTTTTTTTTACACTCAGGCCGC
TTTTTTTTTTCACACTCAGGCCG
TTTTTTTTTTCAGGCCACCAAC
TTTTTTTTTTCGTCTGTACAAAC
TTTTTTTTTTAGAACATCTCATC
TTTTTTTTTTAGAACTGCTCATC
TTTTTTTTTTTGAATTTGATGA
TTTTTTTTTTTGTGTTGATGA
```

DPB1

35

40

45

50

55

```
TTTTTTTTTTCAACCGGGAGGAG
TTTTTTTTTTCAACCTGGAGGAG
TTTTTTTTTTTCATCCTGGAGGAG
TTTTTTTTTTTGCTGGGGGTCA
TTTTTTTTTTGGCCTGACGAGGA
TTTTTTTTTTAACTACGAGCTGG
TTTTTTTTTTTCCAGAGAATTAC
TTTTTTTTTTTGCCGTAACGGT
TTTTTTTTTTTCCAGTACTCCTC
TTTTTTTTTTTAGTGCCGGACAGG
TTTTTTTTTTTACCCCCAGCAGG
TTTTTTTTTTTAGAGAATTACGTG
TTTTTTTTTTTCCAGTACTCCGC
TTTTTTTTTTTGCAATCCTGCCGT
TTTTTTTTTTTCGGGAGGAGCTCG
TTTTTTTTTTTCAGCCAGAAGGAC
TTTTTTTTTTTATTGCCGGACAGG
TTTTTTTTTTTCTGCAGCGCCGAG
TTTTTTTTTTTGCGCGTACTCCTC
TTTTTTTTTTTACAGAATTACCTT
TTTTTTTTTTTAAAGTGTACCAG
TTTTTTTTTTTATCCTGGAGGAGA
TTTTTTTTTTTGGTCATGGGCCCG
TTTTTTTTTTTGGGAGGAGTACGC
TTTTTTTTTTTGGGGCGGCCTGA
```

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTAAAAGGTAATTCT
TTTTTTTTTTCTGCCGTAACGG
TTTTTTTTTTTGTGTCTGCATA
TTTTTTTTTTTGGCTGTTCCAGTA
TTTTTTTTTTTGTCCCTGGTACAC
TTTTTTTTTTTCTGCAGCGCCGA
TTTTTTTTTTTCTGGAGGGGGA
TTTTTTTTTTTGAGGTCCTTCTGG
TTTTTTTTTTTCAACCGGCAGGAG
TTTTTTTTTTTGTGTCTGCATAC
TTTTTTTTTTTCGGGAGCAGTTCCG
TTTTTTTTTTTGACCTGCG-AGCG
TTTTTTTTTTTCAGAGAATTACCT
TTTTTTTTTTTGGGTAGAAATCC
TTTTTTTTTTTACGTGCACCAG
TTTTTTTTTTTCGCTGCAGGGTCA
TTTTTTTTTTTAGCCAGAAGGACA
TTTTTTTTTTTGTTCCAGTAGTCC
TTTTTTTTTTTGGCCTGCTGCGGA
TTTTTTTTTTTGCAGCGCCGAGG
TTTTTTTTTTTACTACGAGCTGGT
TTTTTTTTTTTCTGGGCGGCCTG
TTTTTTTTTTTACAGCGACGTGGG
TTTTTTTTTTTGCCGGACAGGAT
TTTTTTTTTTTCTGCCGTCCCTGG
TTTTTTTTTTTCATGGGCCCGACC
TTTTTTTTTTTGTCCATTAAACG
TTTTTTTTTTTGTAAGTGGTACAC
TTTTTTTTTTTAAGGACCTCCTGG
TTTTTTTTTTTCTCCTGGAGGAGA
TTTTTTTTTTTGAGAATTACGTGT
TTTTTTTTTTTCCTGATGAGGTGT
TTTTTTTTTTTCACAGGAGGAGCA
TTTTTTTTTTTGCCGTCCCTGGT
TTTTTTTTTTTGGGAGGAGTTCCG
TTTTTTTTTTTGGACAGGAGGAA
TTTTTTTTTTTACCCTGCAGCGTC
TTTTTTTTTTTCCGCCCGGAACCTC
TTTTTTTTTTTGCTGCAGGGTCAC
TTTTTTTTTTTACAGGACTATCCA
TTTTTTTTTTTGCGTACTCCTGCC
TTTTTTTTTTTCCGTAAGTGGTGC
TTTTTTTTTTTGCAGGAATGCTAC
TTTTTTTTTTTCCAGGCAGCATTCT
TTTTTTTTTTTAACCGGGAGGAG
TTTTTTTTTTTGGCCTCAGGCGGA
TTTTTTTTTTTACTACGAGCTGGG
TTTTTTTTTTTATGAGGTGTAAGT
TTTTTTTTTTTATACATCTACAAC
TTTTTTTTTTTAACTGGTACACT
TTTTTTTTTTTCACGTAATTCTCT
TTTTTTTTTTTAGCATTCTGCGG
TTTTTTTTTTTACTGGTACACTTA
TTTTTTTTTTTGGCAATGCCCGCT
TTTTTTTTTTTGCTTCGTGCTGGG
TTTTTTTTTTTCGCCCGGAACCTCT
TTTTTTTTTTTACAGGACTGTCCA
TTTTTTTTTTTCTCCAGGAGGT
TTTTTTTTTTTCCCTCTGGCTGTT
TTTTTTTTTTTGTTCCAGTACTCC

- 50 -

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTGCGCTGCAGGGTC
TTTTTTTTTTAACCTGGAGGAGA
TTTTTTTTTTTCCTGCCGTAAC
TTTTTTTTTTACGCTGCAGGGTC
5 TTTTTTTTTTCCACAGAATTACC
TTTTTTTTTTCCAGAGAATTACG
TTTTTTTTTTGCGCCGAGTCCAGC
TTTTTTTTTTAACAGGCAGGAGT
TTTTTTTTTTTCCTCCAGGATGT
10 TTTTTTTTTTAACCGGCAGGAGT
TTTTTTTTTTCTCCAGAGAATTA
TTTTTTTTTTGTTCCAGTACACC
TTTTTTTTTTCTCCTGTAGGAGA
TTTTTTTTTTTACCTTTCCAG
15 TTTTTTTTTTGGAGGAGTTCGTG
TTTTTTTTTTGAGGAGCTCGTGC
TTTTTTTTTTGCCGTAACCTGGT
TTTTTTTTTTGCCCGCTCCTCCT
20 TTTTTTTTTTCGTCCCTGGAAAA
TTTTTTTTTTGCCGTCCCTGGAA
TTTTTTTTTTCCCCTCCAAGAAG
TTTTTTTTTTGCTGCCTGGGTAG
TTTTTTTTTTCCAGTAGTCCTC
TTTTTTTTTTATTCTGCGGTAA
25 TTTTTTTTTTCCTGGAAAAGGTA
TTTTTTTTTTTCGTCCCTGGTACA
TTTTTTTTTTCTCCTCCAGGAAG
TTTTTTTTTTCTGATTCTGCC
TTTTTTTTTTATCTCCCTGTCTG
30 TTTTTTTTTTGAAGGACAACCTG
TTTTTTTTTTTCGTGCACCAGTTA
TTTTTTTTTTTCGGACAGGGTATG
TTTTTTTTTTTCGGACAGGATATG
TTTTTTTTTTGCACTCGGCGCTG
35 TTTTTTTTTTACACGTAATTCTC
TTTTTTTTTTTCGTAACCTGGTACA
TTTTTTTTTTAATGACCCCCCAG
TTTTTTTTTTTCTCTCCAGGAAG
35 TTTTTTTTTTCAGCGACGTGGGA
40 TTTTTTTTTTCCTGCCGGTTGT
TTTTTTTTTTGAAGGACATCCTG
TTTTTTTTTTGAAGGACCTCCTG
TTTTTTTTTTGTTCCAGTACAC
45 TTTTTTTTTTCAGAAGGACAACC
TTTTTTTTTTGCCTGATGAGGTG

DQA1

TTTTTTTTTTTCAAGAGGCAAC
50 TTTTTTTTTTCATAAGAGGCAAC
TTTTTTTTTTTGAACAC.AGGCAAC
45 TTTTTTTTTTTACATCCTCATCTG
TTTTTTTTTTTGAGTGCCATTGC
TTTTTTTTTTTCAGCCACAATGTC
55 TTTTTTTTTTTACAATCCCAGGGC
TTTTTTTTTTTACAACCCAGGGC
TTTTTTTTTTTGTGGGCATTGTGG
50 TTTTTTTTTTTATGGGCATTGTGG
TTTTTTTTTTTCCAACACCCTCAT
60 TTTTTTTTTTTAGACTGTGGTCTG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTCCAACATCCTCAT
TTTTTTTTTTTGGCCACAGACAA
TTTTTTTTTTTCATGGGCAATTGTG
TTTTTTTTTTTAAACATCCTCATCT
TTTTTTTTTTTCAACACCCCTCATT
TTTTTTTTTTTGACTGTGGTCTGC
TTTTTTTTTTTAGCACTGGGGACT
TTTTTTTTTTTCTTAGATTGACC
TTTTTTTTTTTAGATTGACC
TTTTTTTTTTTCGATGTTCAAGTT
TTTTTTTTTTTCAATCCCAGGGCG
TTTTTTTTTTTCCTCGGATGATGA
TTTTTTTTTTTCCACATAGAACT
TTTTTTTTTTTAAATTCATGGGTG
TTTTTTTTTTTCAGCCACAATGCC
TTTTTTTTTTTCACCATAAGAGGC
TTTTTTTTTTTCTCCTCCTTCTG
TTTTTTTTTTTAACTCTCCTCAG
TTTTTTTTTTTAAATCTCATCAG
TTTTTTTTTTTCTCCTCCTTCTG
TTTTTTTTTTTGTGAGCCACAATG
TTTTTTTTTTTCATTCTCTCTC
TTTTTTTTTTTCTTCTCCTTCT
TTTTTTTTTTTATAACTCTCCTCA
TTTTTTTTTTTGAGGCTCATCCAG
TTTTTTTTTTTCAGGCTGTCCAG
TTTTTTTTTTTATGTTGACCACAG
TTTTTTTTTTTAGTGCCACCACA
TTTTTTTTTTTGAACATCCTGATT
TTTTTTTTTTTGGACCTGGAGAAG
TTTTTTTTTTTCCCTCTGGCCAGT
TTTTTTTTTTTCCCTCTGGGR-AGT
TTTTTTTTTTTACACCGTAAGA
TTTTTTTTTTTAGAAGATTGACC
TTTTTTTTTTTGAAGTGGCCAGAG
TTTTTTTTTTTGCTACAACCTAC
TTTTTTTTTTTCAGTCTACGGTC
TTTTTTTTTTTCAGTCTTATGGTC

40 DQB1

TTTTTTTTTTTATCTTGACAGGA
TTTTTTTTTTTGGCTGGGGTGCTC
TTTTTTTTTTTGGGTACCGCCCG
TTTTTTTTTTTCTGGGGCCGCTG
TTTTTTTTTTTCTCGGCGCTAGGC
TTTTTTTTTTTGTATCTGGTCACA
TTTTTTTTTTTAACTACGAGGTGG
TTTTTTTTTTTCCAGTACTCGGCG
TTTTTTTTTTTCGGTTATAGATGT
TTTTTTTTTTTGCAAGTCTGGAG
TTTTTTTTTTTGGACACAACGCC
TTTTTTTTTTTCTGGGGCTGCCTG
TTTTTTTTTTTGGCCTTAACTGG
TTTTTTTTTTTGTGTCTGCATAC
TTTTTTTTTTTGTGCGAAAGGGCT
TTTTTTTTTTTGGGTGTATCGGGT
TTTTTTTTTTTCCAGTACTCGGCA
TTTTTTTTTTTGTAGACATCTCCA
TTTTTTTTTTTAGGAAACGGGCGG

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTTACACCCCGCACG
TTTTTTTTTTTCCGCTCGGGTCC
TTTTTTTTTTTAGCATCACCAGGA
TTTTTTTTTTTCCAGTTTAAGGGC
TTTTTTTTTTTATAGCCACAAGGA
TTTTTTTTTTTGTATGCAGACACA
TTTTTTTTTTTCCAGTACTCGGC
TTTTTTTTTTTAGCGCACGATCTC
TTTTTTTTTTTGGACATCCTGGAG
TTTTTTTTTTTGGGGCTGCCTGA
TTTTTTTTTTTGTAGAAAGGGCT
TTTTTTTTTTTCAGGAGCCCTTTC
TTTTTTTTTTTGTCTCTTCTGG
TTTTTTTTTTTACACCCCGCACGC
TTTTTTTTTTTGGTTTCGGAATG
TTTTTTTTTTTAACGGGACAGAGC
TTTTTTTTTTTGCTGGGGCCGCCT
TTTTTTTTTTTGAGGATTTCTGT
TTTTTTTTTTTGAGAGGAGTACGC
TTTTTTTTTTTACATCAAAGTCC
TTTTTTTTTTTGCCAGGAGGAGAC
TTTTTTTTTTTGTACTCGGCGGCA
TTTTTTTTTTTCGCCAGTTGTCTC
TTTTTTTTTTTAGGGGGGTGGACA
TTTTTTTTTTTAGATGTATCTGGT
TTTTTTTTTTTGGGGGAGTTCCG
TTTTTTTTTTTGTCTCCTCCTGG
TTTTTTTTTTTCACTCTGTCCA
TTTTTTTTTTTGGAATGATCAGGA
TTTTTTTTTTTATGGGGTCGCCGC
TTTTTTTTTTTCAGATCAAAGTCC
TTTTTTTTTTTAACGGGACCGAGC
TTTTTTTTTTTAGGAGTACGTGCG
TTTTTTTTTTTATGTGACCAGATA
TTTTTTTTTTTAGGGGCGGCCTGT
TTTTTTTTTTTCGCCGTTGTCTC
TTTTTTTTTTTGTAAACCAGACAC
TTTTTTTTTTTGTGAAGTAGCACA
TTTTTTTTTTTAGCGGCGACCCCA
TTTTTTTTTTTACACCTGTCCA
TTTTTTTTTTTGTGTGACCAGATA
TTTTTTTTTTTGGACCTTCCAGA
TTTTTTTTTTTATCGGGTGGTGAC
TTTTTTTTTTTGTAAAGGGCCTG
TTTTTTTTTTTGAAGTAGCACAG
TTTTTTTTTTTGCTCCAAGTGGTA
TTTTTTTTTTTCCTTAACTGGTA
TTTTTTTTTTTAGGAGGACGTGCG
TTTTTTTTTTTCGTGCTGGGGCT
TTTTTTTTTTTCGCTGCTGGGGCT
TTTTTTTTTTTCCAAGGAAGATCA
TTTTTTTTTTTACCGCGCGGTGAC
TTTTTTTTTTTGCCCTTAACTGG
TTTTTTTTTTTGGTCACACCCCG
TTTTTTTTTTTGGGAGTTCGGGGC
TTTTTTTTTTTAGGAGGAGACAAC
TTTTTTTTTTTGGGTGGACACAAC
TTTTTTTTTTTCTGCTCGGTGAC
TTTTTTTTTTTGGGGCGGCTTGA
TTTTTTTTTTTGCGCACGTCTCC

5

TTTTTTTATAGGATTCGTGTA
TTTTTTTATGCCTTAACTGGA

10

DRB345

5

TTTTTTTTTGTACCTGGACAGA
TTTTTTTTTGTTCCTGGAGAGA
TTTTTTTTTACACTCATACTTA
TTTTTTTTTACACTCAGACTTA

10

15

TTTTTTTTTCTGGAGCAGGC
TTTTTTTTTCTGAAGCGCGCGT
TTTTTTTTTAAATCTGCACAGAG
TTTTTTTTTAGGGCCCGCCTGT
TTTTTTTTTAGGACACTCTGGA

15

20

TTTTTTTTTGTGTAACCTCTC
TTTTTTTTTCTGTGAAGCGCA
TTTTTTTTTGGGGCCGGGCTGT
TTTTTTTTTCTTCCAGGATGT
TTTTTTTTTAACTACGGAGTTG

20

25

TTTTTTTTTCAAGAAACATGGT
TTTTTTTTTAAACCAGGAGGAG
TTTTTTTTTGAAGCTCTCCAC
TTTTTTTTTGGGGCGGCCTGTC
TTTTTTTTTGCGGCGCGCGTGT

25

30

TTTTTTTTTCTTGGAGCTG
TTTTTTTTTCTCTTCTGGC
TTTTTTTTTAACTACGGGGTTG
TTTTTTTTTGTATCTGATCAGG
TTTTTTTTTGGCCAGGTGGACA

30

35

TTTTTTTTTGCCCCAGCTCCGT
TTTTTTTTTGGTTCTGGAGAG
TTTTTTTTTGTGGAAGCGCACG
TTTTTTTTTGTGTCTGCACTAG
TTTTTTTTTGCTCCACTTGGCA

35

40

TTTTTTTTTACGGGGTTGGTG
TTTTTTTTTCCGGTTCTGCACA
TTTTTTTTTCCAGTACTCGGC
TTTTTTTTTGTCCACCTCGGC
TTTTTTTTTCTTCTGGCCGT

40

45

TTTTTTTTTGGTGTCCACCAGG
TTTTTTTTTACTCCGTAGTTGT
TTTTTTTTTCACTCAGACTTAC
TTTTTTTTTGATGCTAGAAACA
TTTTTTTTTGTGGAATGGAGAG

45

50

TTTTTTTTTAAACCAAGAGGAG
TTTTTTTTTGTTCGGGAATGGC
TTTTTTTTTGTATCTGCACTAG
TTTTTTTTTACCTCCTGGTCTG
TTTTTTTTTAGCCAACAGGACT

50

55

TTTTTTTTTGCGGTTCTGCAG
TTTTTTTTTCCGCGCCGGGTGG
TTTTTTTTTGTAAACCTCTCCA
TTTTTTTTTCTGATCAGGCTCC
TTTTTTTTTCCAGGACTCGGC

55

TTTTTTTTTAAACATTACAGA
TTTTTTTTTCCGGCCCTGGTGG
TTTTTTTTTGTTCGGGAACGGC
TTTTTTTTTGCGGCCCGCCTGT
TTTTTTTTTCTGGAAGACAC

60

TTTTTTTTTGCCGGGTGGACAA

- 54 -

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTCTGCTCCAGGATG
TTTTTTTTTCAACTACTGCAGA
TTTTTTTTTGTACCTGGAGAGA
TTTTTTTTTACCTCTCCACTCC
5 TTTTTTTTTGTGAAGCTCTCCA
TTTTTTTTTCCGCGGCGCGCGT
TTTTTTTTTCTGATCAGGTTCC
TTTTTTTTTAATGGGACGGAGC
TTTTTTTTTATGGAAGTATCT
10 TTTTTTTTTCTGCAGTAGGTG
TTTTTTTTTCCGGGCCGCGGTGG
TTTTTTTTTCTGTGCAGGAACC
TTTTTTTTTCCAAGAGGAGGAC
TTTTTTTTTCAATTACTGCAGA
15 TTTTTTTTTCACCTACTGCAGA
TTTTTTTTTCTGCCTGGATAGA
TTTTTTTTTGTAAATGTCCACC
TTTTTTTTTCACCAGGGCCCGC
20 TTTTTTTTTGCGGTACCTGGA
TTTTTTTTTCCTGCAGCACCCAC
TTTTTTTTTGCGGCGCGCCTGT
TTTTTTTTTCCAGGACTCGGCA
TTTTTTTTTGACACAACCTACGG
25 TTTTTTTTTGATACAACCTACGG
TTTTTTTTTACTCAGACTTACA
TTTTTTTTTGAGACTTACACA
TTTTTTTTTACGGGGTTGTGG
TTTTTTTTTGTAGTTGTCCACC
TTTTTTTTTAACCAGGAGGAGT
30 TTTTTTTTTAACCAAGAGGAGT
TTTTTTTTTCCACAGCCCCGT
TTTTTTTTTCAGCCAGAAGGAC
TTTTTTTTTGGAGGAGTTCCTG
TTTTTTTTTGAACCTCCTCTGG
35 TTTTTTTTTAACCCTCACAGA
TTTTTTTTTGGCGGGGCTGTC
TTTTTTTTTCTCAGAGTCCTG
TTTTTTTTTGTGCAAGCGCAAG
35 TTTTTTTTTCTCTCTGGTCTGT

HLA-A

TTTTTTTTTTCAGTCTGTGAGT
40 TTTTTTTTTCCGCAGGCTCTCT
TTTTTTTTTATGAGGTATTTCT
45 TTTTTTTTTGGACATGGAGGTG
TTTTTTTTTTC-AGGTAGGCTCTC
TTTTTTTTTACTCTTGGGGGC
TTTTTTTTTGGTCGCCAGGTCC
50 TTTTTTTTTGGGAGCCCCGCCA
TTTTTTTTTCCGCTGCTCCGCC
TTTTTTTTTGAAGGCCCAGTC
45 TTTTTTTTTGCAGCCATACATC
TTTTTTTTTCCACTCCACGCAC
55 TTTTTTTTTCACGTTCGACCCA
TTTTTTTTTGGTCTGCCCGAGC
TTTTTTTTTCAGGTAGACTCTC
TTTTTTTTTGGGAGACACGAA
50 TTTTTTTTTCCCGTCCACGCAC
60 TTTTTTTTTGTCCACTCGGTCA

- 55 -

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTATCCAGAGGATGT
TTTTTTTTTTTCGGGATCCGCAGG
TTTTTTTTTTTCGGGACACGGAA
TTTTTTTTTTTGAGGAGGAACAG
TTTTTTTTTTAAGTGAAGGCCCA
TTTTTTTTTTGGGGCTTGGGGAG
TTTTTTTTTTTCACTAACCAG
TTTTTTTTTTTGCCTGGGGGGT
TTTTTTTTTTTCGTCGTAAGCGT
TTTTTTTTTTTAGGTCCACTCGGT
TTTTTTTTTTTGGTAGGCTCTCA
TTTTTTTTTTTGCAGATCCGCAG
TTTTTTTTTTTGTCTCTGGGTCT
TTTTTTTTTTTATCCAGATAATGT
TTTTTTTTTTTCCGTCGTAGGCGT
TTTTTTTTTTTCATATTCGTGT
TTTTTTTTTTTCGGACCCCCCA
TTTTTTTTTTTGCCGATGGACCG
TTTTTTTTTTTGCTGCTCCGCCG
TTTTTTTTTTTAGCGCAGGTCCTC
TTTTTTTTTTTCTACCTGGATGGC
TTTTTTTTTTTGGTATTTCTCAC
TTTTTTTTTTTATATGAAGGCCCA
TTTTTTTTTTTCCGTGCTCCTCCG
TTTTTTTTTTTCCGGCAGTGGAGA
TTTTTTTTTTTCCGACGCCCCCA
TTTTTTTTTTTCCGTGAGGCGGAG
TTTTTTTTTTTAGGAGACAGGAA
TTTTTTTTTTTAGAGCGAGGACGG
TTTTTTTTTTTGACATGGCAGGT
TTTTTTTTTTTCAGCTGCTCCGCC
TTTTTTTTTTTATGAACAGCACGC
TTTTTTTTTTTCCGGGCCCGCAG
TTTTTTTTTTTGCAGCCTGAGAGT
TTTTTTTTTTTGACGGTCATGGC
TTTTTTTTTTTCCGTCGTAAGCGT
TTTTTTTTTTTGAGTATTGGGACC
TTTTTTTTTTTCTGGCCTGTTCT
TTTTTTTTTTTACCTCATGGAGTG
TTTTTTTTTTTAGCCGCCATGTCC
TTTTTTTTTTTCACGTGCCATCCA
TTTTTTTTTTTGGTCCCAGGTTT
TTTTTTTTTTTAGGAGAAGACATA
TTTTTTTTTTTCTGCTGCTCCGCC
TTTTTTTTTTTGACCCAGACCAG
TTTTTTTTTTTCGGCCGGAGCAGT
TTTTTTTTTTTAGGTTCCGTCGGT
TTTTTTTTTTTCATATGCGTCCTG
TTTTTTTTTTTCGTCCTGGGGGGG
TTTTTTTTTTTGCACGTGCGTGGA
TTTTTTTTTTTGGTATTTCTACAC
TTTTTTTTTTTAGGAGCAGAGATA
TTTTTTTTTTTCCCGAACCTCGT
TTTTTTTTTTTGCCACATGGGCCG
TTTTTTTTTTTAGCAGGAGGAGCC
TTTTTTTTTTTATCCAGATGATGT
TTTTTTTTTTTGGATGGGGAGCAC
TTTTTTTTTTTGCCTGGCGCTTC
TTTTTTTTTTTAGCTTGTAAGTG
TTTTTTTTTTTGATAATGTATGGC

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTTACACCCTCCAG
TTTTTTTTTTTCTACGTGGACAAC
TTTTTTTTTTTCGAGCGAACCTGG
TTTTTTTTTTTCGAGAC,AGCCTGC
5 TTTTTTTTTTGGGCTACGTGGAC
TTTTTTTTTTTACCACCAGTACGC
TTTTTTTTTTTGAGGATGTATGGC
TTTTTTTTTTTGATCTCAGCCGCC
TTTTTTTTTTTGATCTGAGCTGCC
10 TTTTTTTTTTGATGATGTATGGC
TTTTTTTTTTTATACCTGGAGAAC
TTTTTTTTTTTGATGTATGGCTGC
TTTTTTTTTTTCCGCAGGTCTC
TTTTTTTTTTTGAGCAGAGATAAA
15 TTTTTTTTTTGGGCTGGGAAGAC
TTTTTTTTTTTGATGGGCAGGACT
TTTTTTTTTTTCACTTCCCTGT
TTTTTTTTTTTCCCACGATGTGGA
20 TTTTTTTTTTAGTCATATGCGTT
TTTTTTTTTTTGGCGGACATGGCG
TTTTTTTTTTTGCTCCGCCCTCACG
TTTTTTTTTTTCGTCGTAAAGCGTT
TTTTTTTTTTTGATC,ATGTTTGGC
25 TTTTTTTTTTCACGGACGCCCCC
TTTTTTTTTTTGCTCCTCCTGCTC
TTTTTTTTTTTACTCACCGAGTGG
TTTTTTTTTTTAGTCATATGTGC
TTTTTTTTTTTGGTCTGAGCTGCC
TTTTTTTTTTTCCCACTTGCCT
30 TTTTTTTTTTGCCCACTCACAGA
TTTTTTTTTTTGGCTCAC.ATCACC
TTTTTTTTTTTGCTCTTGACCGC
TTTTTTTTTTTGAGAGCCTGCGGA
TTTTTTTTTTTGGAAACACACGGAA
35 TTTTTTTTTTCGGAACACACGGAA
TTTTTTTTTTTCGTAAGCGTCCTG
TTTTTTTTTTTGCCGGTGCGTGGA
TTTTTTTTTTTGCCGCATGGGCCG
TTTTTTTTTTTCCAGAGCGAGGAC
40 TTTTTTTTTTCCCAACGGGCGCGC
TTTTTTTTTTTCGAGTGCGTGGAG
TTTTTTTTTTTGCGAACCTGGGA
TTTTTTTTTTTCGGGTACCAGCGG
TTTTTTTTTTTGAAGCGGGGCTC
45 TTTTTTTTTTGGCGGCCCGTTGG
TTTTTTTTTTTCTGGGTC,AGGGC
TTTTTTTTTTTGCCCTATGGGCCG
TTTTTTTTTTTCCATCCCGCTGCC
TTTTTTTTTTTAGCTCAGACCACC
50 TTTTTTTTTTGTCGTAAGCGTCC
TTTTTTTTTTTCCCGGCCGCGGGA
TTTTTTTTTTTGGTCCCAATACTC
TTTTTTTTTTTCGTCCCAATACTC
TTTTTTTTTTTGTCTCACACCAT
55 TTTTTTTTTTCTCTGATGGT
TTTTTTTTTTTCCCACTTGTGCT
TTTTTTTTTTTCCTGACCCAGACC
TTTTTTTTTTTGAGAGCCCGCCC
TTTTTTTTTTTGAGTGCGTGGAGT
60 TTTTTTTTTTACATCATCTGGA

- 57 -

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTGATCCGCAGGTTCT
TTTTTTTTTTTAGAGCAGGAGAG
TTTTTTTTTTTCTGGCAGCGGGA
TTTTTTTTTTTCATGGAGTGAGA
TTTTTTTTTTTCCGGCCGCGGAA
TTTTTTTTTTTCCAGGACACGGAG
TTTTTTTTTTTCCGGGACACGGAG
TTTTTTTTTTTGCAGCCACACATC
TTTTTTTTTTTGGATGGTGTGAGA
TTTTTTTTTTTAACATCATCTGGA
TTTTTTTTTTTCTCTCTCCACAT
TTTTTTTTTTTGGGCGGAGCAGT
TTTTTTTTTTTGCAGGGGATGGA
TTTTTTTTTTTTCGCAGGAAGCGCC
TTTTTTTTTTTGGCCGTCATGGCG
TTTTTTTTTTTATGCGTCTTGGGG
TTTTTTTTTTTATGCGTCTTGGGG
TTTTTTTTTTTCCCTGTCTCC
TTTTTTTTTTTCAGGGTGGCCTC
TTTTTTTTTTTGAGGAGGAACAGC
TTTTTTTTTTTGCAGGAGGTGCGC
TTTTTTTTTTTCAGCCAACATCC
TTTTTTTTTTTACTTCTGGAAGGT
TTTTTTTTTTTCTCTGACGGT
TTTTTTTTTTTGGAGAAGAGATAC
TTTTTTTTTTTATTCCGTGTCTCC
TTTTTTTTTTTCAATCTGTGAGT
TTTTTTTTTTTGGCCCGTCGGCGC
TTTTTTTTTTTTCGGCGGACATGGC
TTTTTTTTTTTACAAGCTGTGAG
TTTTTTTTTTTTCGAACTGCGTGTG
TTTTTTTTTTTTCGAGCTCCGTGTC
TTTTTTTTTTTACTCCAGCACCG
TTTTTTTTTTTCTACGTGGACGAC

HLA-C

TTTTTTTTTTTGTAGCTGGGAGCC
TTTTTTTTTTTATCACACAGCCA
TTTTTTTTTTTAGGCTCTCCGCTC
TTTTTTTTTTTGGAGTGGGAGCAG
TTTTTTTTTTTTCACACCCTCCAG
TTTTTTTTTTTACTCCACGCACAG
TTTTTTTTTTTGCCGTCTGAGCG
TTTTTTTTTTTTCGCGCAGAACCCC
TTTTTTTTTTTAGTAGCCGCGCAG
TTTTTTTTTTTGGAGCGGACAGCC
TTTTTTTTTTTCAGGTAGGCTCTC
TTTTTTTTTTTGGTTCGGGGCTCC
TTTTTTTTTTTGCCCAAGCCCTC
TTTTTTTTTTTGGGCATGACCAGT
TTTTTTTTTTTGCGGCTCCGCGGC
TTTTTTTTTTTCCAGTGGATGTA
TTTTTTTTTTTGGCATGACCAGTT
TTTTTTTTTTTCTCACTCGGTGAG
TTTTTTTTTTTCAAGCCCTCCTCC
TTTTTTTTTTTAGTTTCCGCAGG
TTTTTTTTTTTCAGGTGCGAGCCA
TTTTTTTTTTTCACTGCGATGAAG
TTTTTTTTTTTGGTATGACCAGTT

5

10

15

20

25

30

35

40

45

50

55

TTTTTTTTTTACAGCCAGGCCAG
TTTTTTTTTTGAGGCGGAGCAGC
TTTTTTTTTTGGTTGTAGTAGC
TTTTTTTTTTACCTGCGGAACT
5 TTTTTTTTTTCGGCCCAGGTCTC
TTTTTTTTTTGCTGGACGCAGCC
TTTTTTTTTTCAGGTTCCGCAGG
TTTTTTTTTTCGGCCAGGCACAG
TTTTTTTTTTCCTCCTACACATC
10 TTTTTTTTTTACGGCGGAGCAGC
TTTTTTTTTTAGCGCGCGGAACC
TTTTTTTTTTCACTCGGTCAG
TTTTTTTTTTCACGCCGAGTCC
TTTTTTTTTTGGAGCAGGA,GGG
15 TTTTTTTTTTGGGTATGACCACT
TTTTTTTTTTATACCTGGAGAAC
TTTTTTTTTTGGGTTCTGGGGCTC
TTTTTTTTTTGACCGCTAGGACA
TTTTTTTTTTATCTGAGCCGCTG
20 TTTTTTTTTTCGCGGAGAGCCCC
TTTTTTTTTTCCTGGCGCTTGTA
TTTTTTTTTTCCTGCGGAACTA
TTTTTTTTTTAGCGTCTCCTTCC
TTTTTTTTTTGGCGCCCCGAAC
25 TTTTTTTTTTATGATGTGAGACC
TTTTTTTTTTCTCGGTGTCCTGG
TTTTTTTTTTGTAGTAGCCGCGT
TTTTTTTTTTAGGATGTGAGACC
TTTTTTTTTTGGTAGGCTCTCTG
30 TTTTTTTTTTAGCGTCTTCTTCC
TTTTTTTTTTTCATAGGAGGAAGA
TTTTTTTTTTGACAACCAGGACA
TTTTTTTTTTGCCGCGGGGAGCC
TTTTTTTTTTGGTGAGGGGCTCT
35 TTTTTTTTTTCGAGGGGCTGCCA
TTTTTTTTTTGGGTATAACCACT
TTTTTTTTTTCCAGAATATGTA
TTTTTTTTTTGGGTGCAGGGCTC
TTTTTTTTTTTCGCGCGGAACCC
40 TTTTTTTTTTAGTAGCCGCGTA
TTTTTTTTTTAGCTGCTCTCAGG
TTTTTTTTTTACCGCACGAAGT
TTTTTTTTTTCCGCAGGCTCACT
TTTTTTTTTTGGTGTGAGACCCG
45 TTTTTTTTTTTGGAGCCCCGAAC
TTTTTTTTTTAGCCGCGGGAGCC
TTTTTTTTTTACTGCACGAAGT
TTTTTTTTTTCCGCACGAAGT
TTTTTTTTTTGGTGACGGGCTCC
50 TTTTTTTTTTGCAGCAGGAGC,AG
TTTTTTTTTTGAGTCTCTCATC
TTTTTTTTTTCCGCCGTGTCCGC
TTTTTTTTTTCCACGCACAGGC
TTTTTTTTTTACTCGGTCAGCCT
55 TTTTTTTTTTCACACC,ATCCAGA
TTTTTTTTTTCAACCCCTCCAGA
TTTTTTTTTTGCAGCAGGATGAG
TTTTTTTTTTTCAGCCACCACAGC
TTTTTTTTTTTCGTGGCTGGCCT
60 TTTTTTTTTTACGGCGGAGCAG

5

10

15

20

25

30

35

40

45

50

55

5

10

```
TTTTTTTTTTCTCACACCATCCA
TTTTTTTTTTTGC GGCGGAGCAG
TTTTTTTTTTTCTGAGCCGCCGT
TTTTTTTTTTTGGCGGAGCAGCAG
TTTTTTTTTTTCCGCTGCGGACAC
TTTTTTTTTTTATAACCAGTTCG
TTTTTTTTTTTCACATCCTCCAGA
TTTTTTTTTTTCCGTGTCCGCGGC
TTTTTTTTTTTCGTGGACGACACA
TTTTTTTTTTTCCGCTGTGTCCGC
TTTTTTTTTTTGAAGAATGGAAG
```

Claims

5

10

15

20

25

30

35

40

45

50

55

5

10

CLAIMS

15

20

25

30

35

40

45

50

55

- 5 1. A method of identifying a set of extendible primers for use in
the identification, typing or classification of a nucleic acid of known
sequence having known polymorphisms wherein:
 - i) all possible nucleotide sequences of a chosen length of the
nucleic acid are identified and their corresponding extendible primers,
 - 10 ii) at least one extendible primer is removed from the set
wherein the at least one primer removed identifies a segment of the nucleic
acid identified by at least one other primer.
2. The method of claim 1, wherein between steps i) and ii):
 - 15 ia) potential extensions for each primer are identified with
respect to each nucleotide sequence,
 - ib) for each extendible primer the identified potential extensions
are compared to determine which pairs of sequences can be discriminated
by the primer.
- 20 3. The method of claim 1 or claim 2, wherein a matrix of primers
and pairs of primer extensions is prepared in binary form and is subjected
to analysis by a set covering problem (SCP) algorithm.
- 25 4. The method of claim 3, wherein a greedy algorithm is used.
5. The method of claim 3, wherein a CFT algorithm is used
which involves a Lagrangian relaxation heuristic.
- 30 6. The method of any one of claims 3 to 5, wherein a set of core
primers is selected as a base for analysis by the SCP algorithm.

5

10

7. The method of any one of claims 3 to 6, wherein the set of extendible primers identified by the SCP algorithm is subjected to a redundancy check.

15

8. A set of extendible primers, for use in the identification, typing or classification of a nucleic acid of known sequences having known polymorphisms, identified by the method of any one of claims 1 to 7.

20

9. The set of extendible primers of claim 8, in the form of an array.

25

10. The set of extendible primers of claim 8 or claim 9, for use in the identification, classification or typing of an organism, allele or gene selected from class 1 HLA, class 2 HLA and 16S rRNA.

15

30

11. The set of extendible primers of any one of claims 8 to 10, wherein the primers are arrayed on a surface of a support in such a way that recognisable patterns are formed with different types or alleles.

35

12. A set of extendible primers, for use in the identification, typing or classification of a human leucocyte antigen (HLA) gene as indicated, the set comprising about the number of primers indicated and being capable of distinguishing about the number of alleles indicated:

40

	HLA gene	Number of Alleles	Number of Primers
Class I	HLA-A	91	172
	HLA-B	200	<1000
	HLA-C	47	94
Class II	DPA-1	11	26
	DPB-1	74	130
	DQA-1	17	130
	DQB-1	34	84
	DRB-1	192	<1000
	DRB345	35	94

45

50

55

5

10

15

20

25

30

35

40

45

50

55

13. A set of extendible primers, for use in the identification, typing or classification of 16S rRNA, wherein set comprises about 210 primers and is capable of distinguishing at least about 1207 different sequences.

14. The set of extendible primers of claim 12 or claim 13, wherein the primers have variable segments substantially as set out in appendix 1 or appendix 2.

15. A method of identification, typing or classification of a nucleic acid of known sequence having known polymorphisms, by the use of the set of extendible primers as claimed in any one of claims 8 to 14, which method comprises applying the nucleic acid or fragments thereof to the set of extendible primers under hybridisation conditions, and effecting template-directed chain extension of extendible primers that have formed hybrids.

16. The method of claim 15, wherein the set of extendible primers is provided in the form of an array, and template-directed chain extension is effected using labelled chain-terminating nucleotide analogues.

17. The method of claim 16, wherein template-directed chain extension is effected using four different fluorescently-labelled chain terminating nucleotide analogues, and the results are analysed by total internal reflection fluorescence or confocal microscopy.

18. The method of any one of claims 15 to 17, wherein the nucleic acid is a PCR amplicon.

19. The method of any one of claims 15 to 18, wherein the nucleic acid is HLA Class 1 or HLA Class 2 or 16S rRNA or a PCR amplicon thereof.

5

10

20. The method of any one of claims 15 to 19, wherein a dUTP/uracil-DNA-glycosylase system is used to break the nucleic acid into fragments.

15

5 21. A kit for use in the identification, typing or characterisation of a nucleic acid of known sequence having known polymorphisms, comprising the set of extendible primers as claimed in any one of claims 8 to 14.

20

10 22. The kit of claim 21, comprising also a pair of primers for effecting PCR amplification of the nucleic acid.

25

23. An array of sets of extendible primers as claimed in any one of claims 8 to 14, for the simultaneous identification typing or classification of two or more different HLA genes.

30

24. A computer readable storage medium having a program recorded thereon, wherein the program consists of instructional steps for identifying a set of extendible primers for use in the identification, typing or classification of a nucleic acid of known sequence having known polymorphisms, the steps comprising:

35

i) identifying all possible nucleotide sequences of a chosen length of the nucleic acid and their corresponding extendible primers.

40

ii) removing at least one extendible primer from the set wherein the at least one primer removed identifies a segment of the nucleic acid identified by at least one other primer.

45

50

55

5

- 64 -

10

25. Computer readable program implement consisting of instructional steps for identifying a set of extendible primers for use in the identification, typing or classification of a nucleic acid of known sequence having known polymorphisms, the steps comprising:

15

- 5 i) identifying all possible nucleotide sequences of a chosen length of the nucleic acid and their corresponding extendible primers.
ii) removing at least one extendible primer from the set wherein the at least one primer removed identifies a segment of the nucleic acid identified by at least one other primer.

20

25

30

35

40

45

50

55